


NPN Silicon Planar Transistors

2 N 2220
2 N 2221
2 N 2222

SIEMENS AKTIENGESELLSCHAFT

2 N 2220, 2 N 2221, and 2 N 2222 are epitaxial NPN silicon planar transistors in TO 18 case (18 A 3 DIN 41 876). The collector is electrically connected to the case. The transistors are particularly suitable for use as high-speed switches.

Type	Ordering code
2 N 2220	Q68000-A4573
2 N 2221	Q62702-F134
2 N 2222	Q62702-F135



Approx. weight 0.33 g Dimensions in mm

	2 N 2220		
	2 N 2221	2 N 2222	
Maximum ratings			
Collector-emitter voltage	V_{CEO}	30	V
Collector-base voltage	V_{CBO}	60	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	0.8	A
Junction temperature	T_j	175	°C
Storage temperature range	T_{stg}	-65 to +200	°C
Total power dissipation ($T_{amb} = 25\text{ °C}$)	P_{tot}	0.5	W
Total power dissipation ($T_{case} = 25\text{ °C}$)	P_{tot}	1.8	W
Thermal resistance			
Junction to ambient air	R_{thJA}	≤ 300	K/W
Junction to case	R_{thJC}	≤ 83	K/W

SIEMENS AKTIENGESELLSCHAFT

Static characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$)		2 N 2220	2 N 2221	2 N 2222	
Collector-base breakdown voltage ($I_C = 10\text{ }\mu\text{A}$)	$V_{(BR)CBO}$	> 60	> 60	> 60	V
Collector-emitter breakdown voltage ($I_C = 10\text{ mA}$)	$V_{(BR)CEO}$	> 30	> 30	> 30	V
Emitter-base breakdown voltage ($I_E = 10\text{ }\mu\text{A}$)	$V_{(BR)EBO}$	> 5	> 5	> 5	V
Collector-emitter saturation voltage ($I_B = 15\text{ mA}; I_C = 150\text{ mA}$)	V_{CEsat}	< 0.4	< 0.4	< 0.4	V
($I_B = 50\text{ mA}; I_C = 500\text{ mA}$)	V_{CEsat}	-	< 1.6	< 1.6	V
Base-emitter saturation voltage ($I_C = 150\text{ mA}; I_B = 15\text{ mA}$)	V_{BEsat}	< 1.3	< 1.3	< 1.3	V
($I_C = 500\text{ mA}; I_B = 50\text{ mA}$)	V_{BEsat}	-	< 2.6	< 2.6	V
Emitter cutoff current ($V_{EB} = 3\text{ V}$)	I_{EBO}	< 10	< 10	< 10	nA
Collector cutoff current ($V_{CB} = 50\text{ V}$)	I_{CBO}	< 10	< 10	< 10	nA
($V_{CB} = 50\text{ V}; T_{amb} = 150\text{ }^{\circ}\text{C}$)	I_{CBO}	< 10	< 10	< 10	μA
DC current gain ($V_{CE} = 10\text{ V}; I_C = 0.1\text{ mA}$)	h_{FE}	-	> 20	> 35	-
($V_{CE} = 10\text{ V}; I_C = 1\text{ mA}$)	h_{FE}	> 12	> 25	> 50	-
($V_{CE} = 10\text{ V}; I_C = 10\text{ mA}$)	h_{FE}	> 17	> 35	> 75	-
($V_{CE} = 10\text{ V}; I_C = 150\text{ mA}$)	h_{FE}	20 to 60	40 to 120	100 to 300	-
($V_{CE} = 10\text{ V}; I_C = 500\text{ mA}$)	h_{FE}	-	> 20	> 30	-
($V_{CE} = 1\text{ V}; I_C = 150\text{ mA}$)	h_{FE}	> 10	> 20	> 50	-
Dynamic characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$)					
Collector base capacitance ($V_{CB} = 10\text{ V}; f = 1\text{ MHz}$)	C_{CBO}	< 8	< 8	< 8	pF
Transition frequency ($V_{CE} = 20\text{ V}; I_C = 20\text{ mA};$ $f = 100\text{ MHz}$)	f_T	> 250	> 250	> 250	MHz
Switching times: ($V_{CC} = 20\text{ V}; I_C = 150\text{ mA};$ $I_{B1}\text{ approx. } I_{B2}\text{ approx. } 150\text{ mA}$)					
Delay time	t_d	5	5	5	ns
Rise time	t_r	15	15	15	ns
Storage time	t_s	190	190	190	ns
Fall time	t_f	23	23	23	ns