



SF1A THRU SF1G

SURFACE MOUNT SUPER FAST SWITCHING RECTIFIER

TECHNICAL SPECIFICATION

VOLTAGE: 50 TO 400V CURRENT: 1.0A


FEATURES

- Ideal for surface mount pick and place application
- Low profile package
- Built-in strain relief
- High surge capability
- Open junction chip, silastic passivated
- Super fast recovery for high efficiency
- High temperature soldering guaranteed: 260°C/10sec/at terminal

MECHANICAL DATA

- Terminal: Plated leads solderable per MIL-STD 202E, method 208C
- Case: Molded with UL-94 Class V-O recognized flame retardant epoxy
- Polarity: Color band denotes cathode

DSMA/DO-214AC



	A	B	C	D	
MAX.	.110(2.79)	.177(4.50)	.075(1.90)	.012(0.305)	
MIN.	.100(2.54)	.157(3.99)	.052(1.32)	.006(0.152)	
	E	F	G	H	I
MAX.	.208(5.28)	.090(2.29)	.008(0.203)	.060(1.52)	.035(0.88)
MIN.	.194(4.93)	.078(1.98)	.004(0.102)	.030(0.76)	.027(0.68)

Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Single-phase, half-wave, 60HZ, resistive or inductive load rating at 25°C, unless otherwise stated, for capacitive load, derate current by 20%)

RATINGS	SYMBOL	SF1A	SF1B	SF1C	SF1D	SF1E	SF1G	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	150	200	300	400	V
Maximum RMS Voltage	V_{RMS}	35	70	105	140	210	280	V
Maximum DC Blocking Voltage	V_{DC}	50	100	150	200	300	400	V
Maximum Average Forward Rectified Current ($T_L=110^\circ\text{C}$)	$I_{F(AV)}$	1.0						A
Peak Forward Surge Current (8.3ms single half sine-wave superimposed on rated load)	I_{FSM}	30						A
Maximum Instantaneous Forward Voltage (at rated forward current)	V_F	0.95			1.25			V
Maximum DC Reverse Current ($T_a=25^\circ\text{C}$)	I_R	5.0						μA
(at rated DC blocking voltage) ($T_a=100^\circ\text{C}$)		200						μA
Maximum Reverse Recovery Time (Note 1)	t_{rr}	35						nS
Typical Junction Capacitance (Note 2)	C_J	10						pF
Typical Thermal Resistance (Note 3)	$R_{\theta(ja)}$	40						$^\circ\text{C/W}$
Storage and Operation Junction Temperature	T_{STG}, T_J	-50 to +150						$^\circ\text{C}$

Note:

- 1.Reverse recovery condition $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{rr}=0.25\text{A}$.
- 2.Measured at 1.0 MHz and applied voltage of 4.0V_{dc}
- 3.Thermal resistance from junction to terminal mounted on 5x5mm copper pad area