

CTLSH1-40M322
SURFACE MOUNT
HIGH CURRENT, LOW V_F
SILICON SCHOTTKY DIODE
TINY LEADLESS MODULE™

centralTM
Semiconductor Corp.

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CTLH1-40M322 is a low V_F Schottky diode designed for applications where small size and operational efficiency are prime requirements. With a maximum power dissipation of 1.45W, and a very small package footprint (approximately equal to the SOT-363), this Tiny Leadless Module (TLM) is capable of dissipating up to 4 times the power of similar devices in a comparable surface mount package.

MARKING CODE: CBA

FEATURES:

- High Current ($I_F = 1.0A$)
- Low Forward Voltage Drop ($V_F=0.55V$ Max @ 1.0A)
- High Thermal Efficiency

APPLICATIONS:

- DC/DC Converters
- Reverse Battery Protection
- Battery powered applications
(Cell phones, PDAs, Digital Camera, MP3 Players, etc.)

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)




	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	40	V
Continuous Forward Current	I_F	1.0	A
Peak Repetitive Forward Current, $t_p \leq 1\text{ ms}$	I_{FRM}	3.5	A
Forward Surge Current, $t_p=8\text{ ms}$	I_{FSM}	10	A
Power Dissipation	P_D	1.45	W*
Operating and Storage			
Junction Temperature	T_J, T_{stg}	-65 to +150	$^\circ\text{C}$
Thermal Resistance	Θ_{JA}	86.20	$^\circ\text{C}/\text{W}^*$

ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
$ I_R $	$V_R= 5.0\text{V}$			10	μA
$ I_R $	$V_R= 8.0\text{V}$			20	μA
$ I_R $	$V_R= 15\text{V}$			50	μA
BV_R	$ I_R = 100\mu\text{A}$	40			V
V_F	$ I_F = 10\text{mA}$			0.29	V
V_F	$ I_F = 100\text{mA}$			0.36	V
V_F	$ I_F = 500\text{mA}$			0.45	V
V_F	$ I_F = 1.0\text{A}$			0.55	V
C_J	$V_R= 4.0\text{V}, f= 1.0\text{MHz}$		50		pF
t_{rr}	$ I_F = I_R = 500\text{mA}, I_{rr}= 50\text{mA}, R_L= 50\Omega$		15		ns

* FR-4 Epoxy PC Board with copper mounting pad area of 21 mm²

TLM322 CASE - MECHANICAL OUTLINE



LEAD CODE:


- 1) CATHODE
- 2) ANODE
- 3) ANODE

MARKING CODE: CBA

SYMBOL	DIMENSIONS			
	INCHES	MILLIMETERS	MIN	MAX
A	0.007	0.012	0.17	0.30
B	—	0.005	—	0.125
C	0.075	0.083	1.90	2.10
D	0.075	0.083	1.90	2.10
E	0.006	0.010	0.15	0.25
F	0.026	0.030	0.65	0.75
G	0.031	0.039	0.80	1.00
H	0.000	0.002	0.00	0.05
J	0.024	—	0.60	
K	0.031	0.035	0.79	0.89
L	0.048	0.056	1.22	1.42
M	0.008	0.018	0.20	0.45
N	0.026	—	0.65	
P	0.051	—	1.30	

TLM322 (REV:R2)

Suggested mounting pad layout
for maximum power dissipation
(Dimensions in mm)



For standard mounting refer
to TLM322 Package Details