


The RF Line
UHF Power Transistors

... designed primarily for wideband, large-signal output and driver amplifier stages in the 600 to 1000 MHz frequency range.

- Designed for Class C, Common Base Power Amplifiers
- Specified 28 Volt, 1000 MHz Characteristics:
 - Output Power — 3 to 18 Watts
 - Power Gain — 7.8 dB Min, Common Base
 - Collector Efficiency — 50 to 55%
- Built-in Matching Network for Broadband Operation
- Gold Metallization for Improved Reliability
- Diffused Ballast Resistors
- Hermetic Package for Military/Space Applications

MRA0610H
Series

7.8 dB
600-1000 MHz
3 TO 18 WATTS
BROADBAND
UHF POWER
TRANSISTORS



CASE 393-01, STYLE 1
(HLP-11)

MAXIMUM RATINGS

Rating	Symbol	-3H	-9H	-18H	Unit
Collector-Base Voltage	V _{CES}		50		V _{dc}
Emitter-Base Voltage	V _{EBO}		3.5		V _{dc}
Collector Current — Continuous	I _C	0.5	1.5	2.5	A _{dc}
Operating Junction Temperature	T _J	200			°C
Storage Temperature Range	T _{stg}	- 65 to + 200			°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max			Unit
Thermal Resistance, RF, Junction to Case	R _{θJC}	15	6	4	°C/W

ELECTRICAL CHARACTERISTICS

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Breakdown Voltage (I _C = 20 mA, V _{BE} = 0) (I _C = 60 mA, V _{BE} = 0) (I _C = 100 mA, V _{BE} = 0)	MRA0610- 3H - 9H -18H	V _{(BR)CES}	50 50 50	— — —	— — —	V _{dc}
Emitter-Base Breakdown Voltage (I _E = 0.25 mA, I _C = 0) (I _E = 0.75 mA, I _C = 0) (I _E = 1.25 mA, I _C = 0)	MRA0610- 3H - 9H -18H	V _{(BR)EBO}	3.5 3.5 3.5	— — —	— — —	V _{dc}
Collector Cutoff Current (V _{CB} = 28 V, I _E = 0)	MRA0610- 3H - 9H -18H	I _{CBO}	— — —	— — —	0.5 1.5 2.5	mA _{dc}

ON CHARACTERISTICS

DC Current Gain (I _C = 100 mA, V _{CE} = 5 V) (I _C = 300 mA, V _{CE} = 5 V) (I _C = 500 mA, V _{CE} = 5 V)	MRA0610- 3H - 9H -18H	h _{FE}	10 10 10	— — —	100 100 100	—
---	-----------------------------	-----------------	----------------	-------------	-------------------	---

(continued)

MRA0610H Series

7-33-

MOTOROLA SC (XSTRS/R F) 46E D 6367254 0094291 8 I

ELECTRICAL CHARACTERISTICS — continued

Characteristic	Symbol	Min	Typ	Max	Unit	
DYNAMIC CHARACTERISTICS						
Output Capacitance (V _{CB} = 28 V, I _E = 0, f = 1 MHz)	MRA0610- 3H - 9H -18H	C _{ob}	—	—	4.5 10 14	pF
FUNCTIONAL TESTS						
Common-Base Amplifier Power Gain (V _{CE} = 28 V, P _{out} = 3 W, f = 600 MHz and 1 GHz) (V _{CE} = 28 V, P _{out} = 9 W, f = 600 MHz and 1 GHz) (V _{CE} = 28 V, P _{out} = 18 W, f = 600 MHz and 1 GHz)	MRA0610- 3H - 9H -18H	G _{pb}	7.8 7.8 7.8	— — —	— — —	dB
Collector Efficiency (V _{CE} = 28 V, P _{out} = 3 W, f = 600 MHz and 1 GHz) (V _{CE} = 28 V, P _{out} = 9 W, f = 600 MHz and 1 GHz) (V _{CE} = 28 V, P _{out} = 18 W, f = 600 MHz and 1 GHz)	MRA0610- 3H - 9H -18H	η _c	50 55 55	— — —	— — —	%

TYPICAL CHARACTERISTICS

Note: Divide by I_C² to obtain metal lifetime in hours.

