


Aluminum Capacitors



FEATURES

- Polarized aluminum electrolytic capacitors
- SMD style
- Miniature dimension
- Extended temperature range: 105 °C
- Reflow soldering
- RoHS compliant


RoHS
COMPLIANT

QUICK REFERENCE DATA		
DESCRIPTION	UNIT	VALUE
Nominal case size (Ø D x L)	mm	4 x 5.3 to 10 x 10
Rated capacitance range C _R	µF	0.1 to 470
Capacitance tolerance	%	± 20
Rated voltage range	V	16 to 50
Category temperature range	°C	- 40 to + 105
Load life	h	1000
Based on sectional specification		IEC 60384-4/EN 130300
Climatic category IEC 60068		40/105/56

APPLICATIONS

- Industrial electronics, automotive electronics, telecommunication systems
- Smoothing and filtering
- Miniature power supply units, dc-to-dc converters

PACKAGING

- Supplied in blister tape

SELECTION CHART FOR C _R , U _R AND RELEVANT NOMINAL CASE SIZES (Ø D x L in mm)				
C _R (µF)	RATED VOLTAGE (V)			
	16	25	35	50
0.10	→	→	→	4 x 5.3
0.22	→	→	→	4 x 5.3
0.33	→	→	→	4 x 5.3
0.47	→	→	→	4 x 5.3
1.0	→	→	→	4 x 5.3
2.2	→	→	→	4 x 5.3
3.3	→	→	→	4 x 5.3
4.7	→	→	4 x 5.3	5 x 5.3
10	4 x 5.3	→	5 x 5.3	6.3 x 5.3
22	5 x 5.3	→	6.3 x 5.3	6.3 x 5.8
33	→	6.3 x 5.3	6.3 x 5.8	6.3 x 7.7
47	6.3 x 5.3	→	6.3 x 5.8	6.3 x 7.7
100	6.3 x 5.8	6.3 x 7.7	8 x 10	10 x 10
220	6.3 x 7.7	8 x 10	10 x 10	-
330	8 x 10	10 x 10	-	-
470	10 x 10	-	-	-

DIMENSIONS in millimeters									
CASE SIZE CODE	$D \pm \alpha$	$L \pm \alpha$	$A \pm \alpha$	$B \pm \alpha$	$C \pm \alpha$	$E \pm \alpha$	R	N	P
BB	4 ± 0.5	5.3 ± 0.2	1.9 ± 0.2	4.3 ± 0.2	4.3 ± 0.2	1.0 ± 0.2	0.5 ~ 0.8	0.3	0.5
BC	5 ± 0.5	5.3 ± 0.2	2.3 ± 0.2	5.3 ± 0.2	5.3 ± 0.2	1.4 ± 0.2	0.5 ~ 0.8	0.3	0.5
BD	6.3 ± 0.5	5.3 ± 0.3	2.4 ± 0.2	6.6 ± 0.2	6.6 ± 0.2	2.2 ± 0.2	0.5 ~ 0.8	0.3	0.5
AD	6.3 ± 0.5	5.8 ± 0.3	2.4 ± 0.2	6.6 ± 0.2	6.6 ± 0.2	2.2 ± 0.2	0.5 ~ 0.8	0.3	0.5
BM	6.3 ± 0.5	7.7 ± 0.4	2.4 ± 0.2	6.6 ± 0.2	6.6 ± 0.2	2.2 ± 0.2	0.5 ~ 0.8	0.3	0.5
AE	8 ± 0.5	6.2 ± 0.4	3.3 ± 0.2	8.3 ± 0.2	8.3 ± 0.2	2.3 ± 0.2	0.5 ~ 0.8	0.3	0.5
AF	8 ± 0.5	10 ± 0.5	2.9 ± 0.2	8.3 ± 0.2	8.3 ± 0.2	3.1 ± 0.2	0.8 ~ 1.1	0.3	0.5
AG	10 ± 0.5	10 ± 0.5	3.2 ± 0.2	10.3 ± 0.2	10.3 ± 0.2	4.5 ± 0.2	0.8 ~ 1.1	0.3	0.5

ELECTRICAL DATA	
SYMBOL	DESCRIPTION
U_R	rated voltage
C_R	rated capacitance at 120 Hz
$\tan \delta$	max. dissipation factor at 120 Hz
R_{ESR}	max. equivalent series resistance at 120 Hz
I_R	rated alternating current at 120 Hz and upper category temperature

Note

Unless otherwise specified, all electrical values apply at $T_{amb} = 20^\circ C$, $P = 80$ to 120 kPa, $RH = 45$ to 75 %.

ORDERING EXAMPLE

ECB $10 \mu F/35 V, \pm 20 \%$, size 5×5.3 mm


Ordering code: MALSECB00BC210FARK

For Standard Packaging Quantity (SPQ) and Minimum Order Quantity (MOQ) please refer to our price list or contact customer service.

ELECTRICAL DATA AND ORDERING INFORMATION							
U_R (V)	C_R 120 Hz (μF)	DIMENSIONS $D \times L$ (mm)	$\tan \delta$ 120 Hz	R_{ESR} 120 Hz (Ω)	I_R 120 Hz/105 °C (mA)	WEIGHT (g)	CATALOG NUMBER
16	10	4×5.3	0.19	25.20	17	0.12	MALSECB00BB210DARK
	22	5×5.3	0.19	11.45	30	0.17	MALSECB00BC222DARK
	47	6.3×5.3	0.19	5.36	51	0.30	MALSECB00BD247DARK
	100	6.3×5.8	0.19	2.52	64	0.30	MALSECB00AD310DARK
	220	6.3×7.7	0.19	1.15	105	0.37	MALSECB00BM322DARK
	330	8×10	0.19	0.76	425	1.00	MALSECB00AF333DARK
	470	10×10	0.19	0.54	470	1.21	MALSECB00AG347DARK

ELECTRICAL DATA AND ORDERING INFORMATION							
U_R (V)	C_R 120 Hz (μ F)	DIMENSIONS D x L (mm)	$\tan \delta$ 120 Hz	R_{ESR} 120 Hz (Ω)	I_R 120 Hz/105 °C (mA)	WEIGHT (g)	CATALOG NUMBER
25	33	6.3 x 5.3	0.15	6.03	48	0.30	MALSECB00BD233EARK
	100	6.3 x 7.7	0.15	1.99	91	0.37	MALSECB00BM310EARK
	220	8 x 10	0.15	0.90	340	1.00	MALSECB00AF322EARK
	330	10 x 10	0.15	0.60	360	1.21	MALSECB00AG333EARK
35	4.7	4 x 5.3	0.13	36.69	14	0.12	MALSECB00BB147FARK
	10	5 x 5.3	0.13	17.24	24	0.17	MALSECB00BC210FARK
	22	6.3 x 5.3	0.13	7.84	42	0.30	MALSECB00BD222FARK
	33	6.3 x 5.8	0.13	5.22	52	0.30	MALSECB00AD233FARK
	47	6.3 x 5.8	0.13	3.67	63	0.30	MALSECB00AD247FARK
	100	8 x 10	0.13	1.72	296	1.00	MALSECB00AF310FARK
	220	10 x 10	0.13	0.78	435	1.21	MALSECB00AG322FARK
50	0.10	4 x 5.3	0.11	1459	2.3	0.12	MALSECB00BB010HARK
	0.22	4 x 5.3	0.11	663.2	3.4	0.12	MALSECB00BB022HARK
	0.33	4 x 5.3	0.11	442.1	4.1	0.12	MALSECB00BB033HARK
	0.47	4 x 5.3	0.11	310.4	4.9	0.12	MALSECB00BB047HARK
	1.0	4 x 5.3	0.11	145.9	7.2	0.12	MALSECB00BB110HARK
	2.2	4 x 5.3	0.11	66.32	10.7	0.12	MALSECB00BB122HARK
	3.3	4 x 5.3	0.11	44.21	13.1	0.12	MALSECB00BB133HARK
	4.7	5 x 5.3	0.11	31.04	18.1	0.17	MALSECB00BC147HARK
	10	6.3 x 5.3	0.11	14.59	30.8	0.30	MALSECB00BD210HARK
	22	6.3 x 5.8	0.11	6.63	45	0.30	MALSECB00AD222HARK
	33	6.3 x 7.7	0.11	4.42	60	0.37	MALSECB00BM233HARK
	47	6.3 x 7.7	0.11	3.10	63	0.37	MALSECB00BM247HARK
	100	10 x 10	0.11	1.46	295	1.21	MALSECB00AG310HARK

REFLOW SOLDERING CONDITIONS FOR SMD ALUMINUM ELECTROLYTIC CAPACITORS





PROFILE FEATURE			
	SOLDERING CONDITION		
	Ø 4 ~ Ø 10	Ø 12.5	Ø 16
Average ramp-up rate (T _L to T _P)	3 °C/s max.	3 °C/s max.	
Preheat			
Temperature min. (T _s min.)	150 °C	150 °C	
Temperature max. (T _s max.)	200 °C	200 °C	
Time (T _s min. to T _s max.)	60 ~ 150 s	40 ~ 120 s	40 ~ 100 s
T _s max. to T _L			
Ramp-up rate	3 °C/s max.	3 °C/s max.	
Time maintained above			
Temperature (T _L)	217 °C	217 °C	
Time (t _L)	60 ~ 90 s	40 ~ 60 s	
Peak/classification temperature (T _P)	250 °C	240 °C	230 °C
Time within 5 °C of actual peak temperature (T _P)	10 s max.	10 s max.	
Ramp-down rate	3 °C/s max.	3 °C/s max.	
Time 25 °C to peak temperature	8 min max.	8 min max.	

RESISTANCE TO SOLDERING HEAT	
Leakage current	Less than specified value
Capacitance value	Within ± 10 % of initial value
Tan δ	Less than specified value

LOW TEMPERATURE BEHAVIOR (at 120 Hz)				
IMPEDANCE RATIO (Z) T2/(Z) T1	RATED VOLTAGE (V)			
	16	25	35	50
- 25 °C/+ 20 °C	2	2	2	2
- 40 °C/+ 20 °C	4	3	3	3

ADDITIONAL ELECTRICAL DATA		
PARAMETER	CONDITIONS	VALUE
Current		
Leakage current (Test conditions: U _R , 20 °C)	after 2 min at U _R	I _{L2} ≤ 0.01 x C _R x U _R or 3 µA for U _R ≤ 100 V (whichever is greater)
Resistance		
Equivalent series resistance (ESR)	calculated from tan δ _{max} .	ESR = tan δ/2πf C _R

MULTIPLIER OF RIPPLE CURRENT (I _R) AS A FUNCTION OF FREQUENCY	
FREQUENCY (Hz)	I _R MULTIPLIER FOR U _R ≤ 100 V
50	0.70
120	1.00
300	1.17
1000	1.36
≥ 10 000	1.50

TEST PROCEDURES AND REQUIREMENTS		
TEST	PROCEDURE (QUICK REFERENCE)	REQUIREMENTS
Load life	T _{amb} = 105 °C U _R and I _R applied After 1000 h	ΔC/C: ± 25 % of initial value I _L ≤ spec. limit tan δ ≤ 2 x spec. limit
Shelf life	No voltage applied After 1000 h After test: U _R to be applied for 30 min 24 to 48 h before measurement	ΔC/C: ± 25 % of initial value I _L ≤ spec. limit tan δ ≤ 2 x spec. limit



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.