

PFR/GFR series, Thick Film chip resistors



A temperature coefficient of resistance of $\pm 100 ppm/^{\circ}C$ has been achieved for resistance value greater than 1M Ω .

High reliability is maintained: the electrode construction is the same as our thin film chip resistors.


NEW PFR03 series with ultra small size chip resistor.



SPECIFICATIONS

RoHS compliant

Mechanical



Dimension (Inch Size)	PFR03 (0201)	PFR05,GFR05 (0402)
L	0.60 ± 0.03	1.00±0.05
W	$0.30 \!\pm\! 0.03$	0.50 ± 0.05
Р	0.12 ± 0.05	0.20±0.10
Т	0.23 ± 0.03	0.35±0.05

(unit : mm)

Electrical

Туре	PFR03					PFR05			GFR05		
Power	1/20W				Jumper	1/16W			Jumper	1/16W	
Tolerance %(code)	±1%(F) ±5		±5%(J)	±2%(G)±5%(J)		_	±0.5%(D) ±1%(F)		±1%(F)	_	±1%(F) ±5%(J)
Resistance Range(Ω)	10~91	100~1M	3.0~9.1	10~91	100~10M	50m or less	10~97.6	100~1M	1.02M~10M	50m or less	10∼10M
TCR ppm /°C(code)	±300 (S)	±200 (S)	+600∼ −200(S)	±300 (S)	±200 (S)	_	±100 (R)	±50 (Q)	±100 (R)	_	±200 (S)
Resistance Value	E-24/E-96 E-24			_	E-24/E-96			_	E-24/E-96		
Max Operating Voltage	25V					1A	50V			_	50V
Package	15,000pcs/reel or 10,000pcs/reel					10,000pcs/reel			10,000pcs/reel		

- \cdot Please contact us for values lower in resistance than the 10 Ω GFR05 series.
- · Contact us for lead free glass coat products.



PART NUMBER



