


## ULTRA HIGH SPEED SWITCHING APPLICATION

## 1SS226

## ■ Features

- Small Package
- Low forward voltage : $V_F(3) = 0.9$  V(Typ.)
- Fast Reverse Recovery Time : $t_{rr} = 1.6$  ns(Typ.)
- Small Total Capacitance : $C_T = 0.9$  pF(Typ.)

■ Absolute Maximum Ratings  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Rating	Unit
Peak Reverse Voltage	$V_{RM}$	85	V
DC Reverse Voltage	$V_R$	80	V
Peak Reverse Current	$I_{FM}$	300*	mA
Average Rectified Current	$I_o$	100*	mA
Surge Current (10 ms)	$I_{FSM}$	2*	A
DC Forward Current	P	150	mW
Junction Temperature	$T_j$	125	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-55 to + 125	$^\circ\text{C}$

(\*) Unit Rating. Total Rating = Unit Rating  $\times$  0.7.

■ Electrical Characteristics  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Continuous reverse voltage	$V_F$	$I_F = 1.0$ mA		0.6		V
		$I_F = 10$ mA		0.72		
		$I_F = 100$ mA		0.9	1.2	
Reverse current	$I_R$	$V_R = 30$ V			0.1	$\mu\text{A}$
		$V_R = 80$ V			0.5	
Total capacitance	$C_T$	$V_R = 0, f = 1.0$ MHz		0.9	3.0	pF
Reverse recovery time	$t_{rr}$	$I_F = 10$ mA		1.6	4.0	ns

## ■ Marking

Marking	C3
---------	----