

Silicon NPN Power Transistors

2SC3058A

DESCRIPTION

- With TO-3 package
- High voltage ,high speed

APPLICATIONS

- For switching regulator and DC/DC converter applications

PINNING (See Fig.2)

PIN	DESCRIPTION
1	Base
2	Emitter
3	Collector




Fig.1 simplified outline (TO-3) and symbol

Absolute maximum ratings(Ta=25°C)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V _{CB0}	Collector-base voltage	Open emitter	600	V
V _{CEO}	Collector-emitter voltage	Open base	450	V
V _{EBO}	Emitter-base voltage	Open collector	7	V
I _C	Collector current		30	A
P _T	Total power dissipation	T _C =25°C	200	W
T _j	Junction temperature		200	°C
T _{stg}	Storage temperature		-65~200	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	VALUE	UNIT
R _{th j-mb}	Thermal resistance from junction to mounting base	1.0	°C/W

Silicon NPN Power Transistors

2SC3058A

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-emitter breakdown voltage	I _C =10mA ; I _B =0	450			V
V _{(BR)CBO}	Collector-base breakdown voltage	I _C =1mA; I _E =0	600			V
V _{(BR)EBO}	Emitter-base breakdown voltage	I _E =1mA; I _C =0	7			V
V _{CE(sat)}	Collector-emitter saturation voltage	I _C =20A; I _B =4A			1.0	V
V _{BE(sat)}	Base-emitter saturation voltage	I _C =20A; I _B =4A			1.5	V
I _{CBO}	Collector cut-off current	V _{CB} =500V; I _E =0			100	μA
I _{EBO}	Emitter cut-off current	V _{EB} =5V; I _C =0			100	μA
h _{FE-1}	DC current gain	I _C =1A ; V _{CE} =5V	15		50	
h _{FE-2}	DC current gain	I _C =20A ; V _{CE} =5V	10		40	
f _T	Transition frequency	I _C =4A ; V _{CE} =10V		30		MHz
C _{OB}	Collector output capacitance	I _E =0 ; V _{CB} =10V;f=1MHz		420		pF

Silicon NPN Power Transistors

2SC3058A

PACKAGE OUTLINE




Fig.2 Outline dimensions