



# LS4148 / LS4448


Fast Switching Diode

## Features

- ♦ Silicon Epitaxial Planar Diodes
- ♦ Electrical data identical with the devices 1N4148 and 1N4448 respectively
- ♦ Quadro Melf package

## Applications

- ♦ Extreme fast switches



## Mechanical Data

- ♦ Case:QuadroMELF Glass Case (SOD-80)
- ♦ Weight: approx. 34 mg
- ♦ Cathode Band Color: Black

## ■ Absolute Maximum Ratings

(  $T_{amb}=25^{\circ}C$  unless otherwise specified )

Parameter	Test Condition	Symbol	Value	Unit
Repetitive peak reverse voltage		$V_{RRM}$	100	V
Reverse voltage		$V_R$	75	V
Peak forward surge current	$t_p = 1 \mu s$	$I_{FSM}$	2	A
Repetitive peak forward current		$I_{FRM}$	500	mA
Forward current		$I_F$	300	mA
Average forward current	$V_R=0$	$I_{FAV}$	150	mA
Power dissipation		$P_V$	500	mW

## ■ Thermal Characteristics

(  $T_{amb}=25^{\circ}C$  unless otherwise specified )

Parameter	Test Condition	Symbol	Value	Unit
Junction ambient	on PC board 50 mm X 50mm X 1.6mm	$R_{thJA}$	500	K/W
Junction temperature		$T_J$	175	°C
Storage temperature range		$T_{sq}$	-65 to +175	°C

## ■ Electrical Characteristics

(  $T_{amb}=25^{\circ}C$  unless otherwise specified )

Parameter	Test Condition	Part	Symbol	Min.	Typ.	Max.	Unit
Forward voltage	$I_F=5mA$	LS4448	$V_F$	0.62	0.72	V	
	$I_F=50mA$	LS4148			0.86	1	
	$I_F=100mA$	LS4148			0.93	1	
Reverse current	$V_R=20V$		$I_R$			25	nA
	$V_R=20V, T_J=150^{\circ}C$		$I_R$			50	uA
	$V_R=75V$		$I_R$			5	uA
Breakdown voltage	$I_R=100uA, t_p/T=0.01, t_p=0.3ms$		$V_{(BR)}$	100			V
Diode capacitance	$V_R=0, f=1MHz, V_{HF}=50mV$		$C_D$			4	pF
Rectification efficiency	$V_{HF}=2V, f=100MHz$		$\eta_r$	45			%
Reverse recovery time	$I_F=I_R=10mA, I_R=1mA$		$t_{rr}$			8	nS
	$I_F=10mA, V_R=6V, I_R=0.1 \times I_R, R_L=100\Omega$					4	

## ■Typical characteristics

(  $T_{amb} = 25^\circ\text{C}$  unless otherwise specified )




Fig. 1 Forward Current vs. Forward Voltage




Fig. 3 Reverse Current vs. Reverse Voltage




Fig. 2 Forward Current vs. Forward Voltage






Fig. 4 Diode Capacitance vs. Reverse Voltage

## Package Dimensions in mm (inches)



### Mounting Pad Layout



Glass case  
Quadro Melf / SOD 80  
JEDEC DO 213 AA