



Shanghai Lunsure Electronic  
Technology Co.,Ltd  
Tel:0086-21-37185008  
Fax:0086-21-57152769

BAT45

## Features

- Metal-to-silicon junction
- Low turn-on voltage
- Ultrafast switching speed

## Maximum Ratings

- Operating Temperature: -55°C to +125°C
- Storage Temperature: 55°C to +150°C
- Maximum Thermal Resistance; 400°C/W Junction To Ambient


Electrical Characteristics @ 25°C Unless Otherwise Specified

Peak Reverse Voltage	$V_{RM}$	15V	
Forward continuous Current	$I_F$	30mA	$T_A = 25^\circ C$
Junction Temperature	$T_J$	125°C	
Peak Forward Surge Current	$I_{FSM}$	60mA	$T_p \leq 1s,$ $T_A = 25^\circ C$
Maximum Instantaneous Forward Voltage	$V_F$	0.38V 0.50V 1.0V	$I_F = 1mA$ $I_F = 10mA$ $I_F = 30mA$
Maximum DC Reverse Current At Rated DC Blocking Voltage	$I_R$	100nA	$V_R=6.0\text{Volts}$ $T_J = 25^\circ C$
Reverse Breakover Voltage	$V_R$	15V	$I_R = 10\mu A$
Typical Junction Capacitance	$C_J$	1.1pF	Measured at 1.0MHz, $V_R=1V$

Pulse Test: 300μSec pulse width, 2% duty cycle

**30Milliamp Small  
Signal Schottky Diode  
15 Volt**

DO-35



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

# BAT45

Figure 1. Forward current versus forward voltage at different temperatures (typical values)




Figure 2. Forward current versus forward voltage (typical values)




Figure 3. Reverse current versus ambient temperature




Figure 4. Reverse current versus continuous reverse voltage (typical values)

