


# 5X7 Dot Character VFD Module

# CU20029SCPB-T21A

- ❑ 2 Lines of 20 Characters 9mm High
- ❑ High Speed Parallel/RS232 Serial Interface
- ❑ Operating Temp -10°C to +65°C
- ❑ Single 5V Supply
- ❑ High Brightness Blue Green Display
- ❑ ASCII, Katakana & Extended Character Font
- ❑ 8 User Definable Character RAM

The module includes the Vacuum Fluorescent Display glass, driver and micro-controller ICs with refresh RAM, character generator and interface logic. The high speed 8 bit parallel interface is 5V CMOS compatible suitable for connection to a host CPU bus. The asynchronous serial interface accepts baud rates up to 19,200 with or without parity. Two character font tables can be hardware or software selected. User defined characters and many control commands are available.



Dimensions in mm. See full spec for tolerances

## ELECTRICAL SPECIFICATION

Parameter	Symbol	Value	Condition
Power Supply Voltage	V <sub>CC</sub>	5.0VDC +/- 5%	GND=0V
Power Supply Current	I <sub>CC</sub>	700mADC typ.	V <sub>CC</sub> =5V
Logic High Input	V <sub>IH</sub>	2.0VDC min.	V <sub>CC</sub> =5V
Logic Low Input	V <sub>IL</sub>	0.8VDC max.	V <sub>CC</sub> =5V
Logic High Output	V <sub>OH</sub>	2.4VDC min.	I <sub>OH</sub> = -2.0mA
Logic Low Output	V <sub>OL</sub>	0.5VDC max.	I <sub>OL</sub> = 2.0mA
RS232 High Input	V <sub>IH</sub>	3.0VDC min.	V <sub>CC</sub> =5V
RS232 Low Input	V <sub>IL</sub>	-3.0VDC max.	V <sub>CC</sub> =5V

The power on rise time should be less than 50ms. The inrush current at power on can be 2 x I<sub>CC</sub>.

## OPTICAL and ENVIRONMENTAL SPECIFICATIONS

Parameter	Value
Character Size/Pitch (XxY mm)	6.2 x 9.5/7.7 x 14.1
Dot Size/Pitch (XxY mm)	1.0 x 1.1/1.3 x 1.4
Luminance	350 cd/m <sup>2</sup> (100 fL) min.
Colour of Illumination	Blue-Green (Filter for colours)
Operating Temperature	-10°C to +65°C
Storage Temperature	-40°C to +85°C
Operating Humidity (non condensing)	20 to 80% RH @ 25°C

## SOFTWARE COMMANDS

Instruction	D0-D7	Instruction	D0-D7
Back Space	08H	Katakana Font	19H
Horizontal Tab	09H	Escape	1BH
Line Feed	0AH	>> Send User Font	+43H
Form Feed	0CH	>> Position cursor	+48H
Carriage Return	0DH	>> Software Reset	+49H
Clear Display	0EH	>> Luminance	+4CH
Increment Write Mode	11H	>> Flickerless Write	+53H
Vertical Scroll Mode	12H	>> Cursor Blink Speed	+54H
5x7 Block Cursor On	15H	Character Data	20H+
Cursor Off	16H	User Character Data	00H+
International Font	18H		

## TIMING PARAMETERS (min)

Data Set Up To Write	100ns	Subject to change without notice. Detailed specification on request. IUK Doc Ref:3348 Iss.1 6 Apr 01
Write Pulse Width	160ns	
Hold After Write	10ns	

## CHARACTER FONTS

International Font																Additional Katakana Font															
00	10	20	30	40	50	60	70	80	90	A0	B0	C0	D0	E0	F0	80	90	A0	B0	C0	D0	E0	F0								
00				00P`	PEZ	#	A0D	3	EU	-	9	30																			
01	!	1	AQ	a	9	0	1	±	A	N	A	F	Γ	3	#	7	7	2	A												
02	"	2	B	R	b	r	f	≡	q	2	P	0	a	b	0	0	W	"	Y	W	W										
03	#	3	C	S	c	s	l	×	E	3	P	0	a	b	0	0	X	9	↓	5	T	F									
04	\$	4	D	T	d	t	L	÷	0	4	P	0	a	b	0	0	3	0	∞	I	T	F									
05	%	5	E	V	e	v	u	x	0	5	P	0	a	b	0	0	4	0	∞	7	1	3									
06	&	6	F	V	v	u	r	?	1	T	E	0	E	0	E	0	5	0	7	0	2	3									
07	'	7	G	U	u	v	0	E	S	-	0	X	0	0	0	6	0	0	7	7	7	7									
08	(	8	H	X	h	x	e	±	.	E	E	0	E	0	E	0	7	∞	7	7	7	7									
09	)	9	I	V	i	v	h	±	0	1	E	0	E	0	E	0	8	∞	7	7	7	7									
0A	*	:	J	Z	j	z	0	±	a	#	E	0	E	0	E	0	9	∞	7	7	7	7									
0B	+	:	K	L	k	l	±	±	±	±	E	0	E	0	E	0	0	4	4	7	7	7									
0C	,	<	L	\	l	l	±	±	±	±	±	±	±	±	±	±	1	∞	7	7	7	7									
0D	-	=	M	I	m	i	±	±	±	±	±	±	±	±	±	±	2	∞	7	7	7	7									
0E	.	>	N	^	n	^	±	±	±	±	±	±	±	±	±	±	3	∞	7	7	7	7									
0F	/	?	0	l	o	l	o	±	±	±	±	±	±	±	±	±	4	∞	7	7	7	7									

## IDC DATA CONNECTOR

Pin	Sig	Pin	Sig
1	D7	9	/WR
2	D6	10	/CS
3	D5	11	SIN/TEST
4	D4	12	BUSY
5	D3	13	GND (0V)
6	D2	14	GND (0V)
7	D1	15	V <sub>CC</sub> (5V)
8	D0	16	V <sub>CC</sub> (5V)

## PCB JUMPERS (O)PEN (L)INK

Baud	J2	J1	J0
19200	O	O	O
9600	O	O	L
4800	O	L	O
2400	O	L	L
1200	L	O	O
Parity	J4	J3	
EVEN	O	O	
ODD	O	L	
NONE	L	L/O	

## 3 PIN POWER CONNECTOR

Pin	Sig
1	V <sub>CC</sub> (5V)
2	SIN/TEST
3	GND (0V)

Mates with AMP171822-3

**Noritake Sales Office Tel Nos**  
 Nagoya Japan: +81 (0)52-561-9867  
 Canada: +1-416-291-2946  
 Chicago USA: +1-847-439-9020  
 Munchen (D): +49 (0)89-3214-290  
 Itron UK: +44 (0)1493 601144  
 Rest Europe: +49 (0)61-0520-9220  
[www.noritake-itron.com](http://www.noritake-itron.com)