

SSQ-115-04-S-T



SOCKET STRIP SSW & SSQ SERIES

SPECIFICATIONS

For complete specifications see www.samtec.com?SSW or www.samtec.com?SSQ

Insulator Material:
Black Liquid Crystal Polymer (-S & -D) or Black High Temperature Thermoplastic (-T)
Contact Material: Phosphor Bronze
Plating: Au or Sn over 50µ" (1,27µm) Ni



Operating Temp Range: -55°C to +125°C with Gold -55°C to +105°C with Tin

Contact Resistance: 10 mΩ max

Insertion Depth: (3,68mm) .145" to (6,35mm) .250"

Insertion Force: (Single contact only) (-S plating)

Standard= 6oz (1,67N) avg ((0,64mm) .025" SQ pin);

SSW Low Insertion Force= 3oz (0,83N) avg

SSQ Low Insertion Force= 3,3oz (0,92N) avg

Normal Force: Standard= 125grams (4,4N)

Withdrawal Force: (Single contact only) (-S plating)

Standard= 5oz (1,39N) avg ((0,64mm) .025" SQ pin);

SSW Low Insertion Force= 2,6oz (0,72N) avg

SSQ Low Insertion Force= 2,9oz (0,81N) avg

Max Cycles: 100 with 10µ" (0,25µm) Au

Voltage Rating: 550 VAC mated with TSW

RoHS Compliant: Yes

Processing: Lead-Free Solderable: Yes

Note: Some lengths, styles and options are non-standard, non-returnable.

Current Rating:

Ambient Temperature:

SSW mated with TSW:

20°C 5.5A

40°C 5A

60°C 4A

80°C 3A

Mates With: TSW, MTSW, MTLW, LCW, EW, ZW, TSS, ZSS, TSM, TSSH



TYPE STRIP



PIN CENTERS

NO. PINS PER ROW

SSW = Solder Tail

SSQ = Square Tail

-1 = (2,54mm) .100" Centers




01 thru 50

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

www.DataSheet4U.com




www.datasheet4u.com

LEAD STYLE	PLATING OPTION	ROW OPTION	TAIL OPTION	OTHER OPTION
	<p>-F = Gold flash on contact, Matte Tin on tail</p> <p>-G = 20μ" (0,51μm) Gold on contact, Gold flash on tail</p> <p>-T = Matte Tin (-T N/A on LIF contacts)</p> <p>-S = 30μ" (0,76μm) Gold on contact, Matte Tin on tail</p>	<p>-S = Single Row</p> <p>-P = Single Row (Notched to mate with LCW) 36 pins max</p> <p>-D = Double Row</p> <p>-T = Triple Row</p> <p>-Q = Double Row .200" (5,08mm) row space (Outer rows filled only)</p>	<p>-RA = Right Angle (Leave blank for straight pin version)</p>	<p>-LL = Locking Lead</p> <p>Two leads per strip crimped in opposite directions on or near centerline. Available on tails from (2,29) .090" to (7,87) .310" only. N/A with single row 1 or 2 positions.</p> <p>-“XXX” = Polarized (Specify “XXX” as position number)</p>

Straight Pin Versions (Specify “LEAD STYLE” from chart)

LEAD STYLE		SINGLE DOUBLE OR TRIPLE A
Standard Insertion Force	Low Insertion Force*	
-01	-21	(2,64) .104
-02	-22	(4,93) .194
-03	-23	(10,00) .394
-04	-24	(14,83) .584
-06**	N/A	(3,00) .118


* LIF N/A with Tin Plating
**Style -06 N/A with SSQ



Right Angle Versions (Specify “LEAD STYLE” from chart)

LEAD STYLE		SINGLE	DOUBLE	TRIPLE
Standard Insertion Force	Low Insertion Force*	(-S & -P) A	(-D) A	(-T & -Q) A
-02	-22	(2,54) .100	(2,54) .100	(2,54) .100
-03	-23	(7,62) .300	(7,62) .300	N/A
-04	-24	(12,45) .490	N/A	N/A

*LIF N/A with Tin Plating



Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

www.DataSheet4U.com