

Ceramic Capacitors

UHV and FHV Series

Disk with Metal Fitting Type Electrode Ultra High Voltage

CLASS 2 HIGH DIELECTRIC

DC. 20 TO 50kV: UHV-1A TO 12A, 221A TO 253A TYPES

DC. 15 TO 50kV: FHV-1AN TO 12AN, 153AN TYPES

TDK UHV and FHV series high voltage ceramic capacitors feature low dissipation and excellent voltage-capacitance characteristics using patented strontium titanate for dielectric material. They are epoxy-encapsulated to meet requirement of high voltage applications.



FEATURES

- Small size.
- Low dissipation factor.
- Excellent voltage-capacitance characteristics.
- Screw terminals for easy mounting.
- FHV series: High capacitance and low temperature characteristics of capacitance.

APPLICATIONS

High voltage power supplies, laser equipment.

INITIAL CHARACTERISTICS


Series	UHV	FHV
Operating temperature range	-30 to +85°C	-30 to +85°C
Rated voltage	DC. 20 to 50kV	DC. 15 to 50kV
Insulation resistance	100,000MΩ min.	100,000MΩ min.
Nominal capacitance range	100 to 4,000pF	700 to 7,000pF
Capacitance tolerance	±10%	±10%
Dissipation factor(tanδ)	0.2% max.	0.2% max.
Capacitance temperature characteristics	Z5T: +22, -33%[+10 to +85°C, 25°C]	Y5S: ±22%[-30 to +85°C, 25°C]
AC Corona starting voltage	3PC* max. at 50% of rated voltage min.(50Hz rms)	3PC* max. at 50% of rated voltage min.(50Hz rms)
Withstanding voltage	No breakdown at 1.5 times of rated voltage, 60s(in oil)	No breakdown at 1.5 times of rated voltage, 60s(in oil)

* PC: Pico coulomb


SHAPES AND DIMENSIONS

UHV-1A to 12A

FHV-1AN to 12AN



UHV-221A to 253A



Dimensions in mm

MARKING

Item	Marking example
1. Part No.	1 → UHV-5A
2. Nominal capacitance and tolerance code	2 → 172K
3. Rated voltage	3 → 30kV
4. Manufacturer's name (TDK or TDK logo mark)	4 → TDK
5. Lot No.	5 → 1234

• For more information about products with other capacitance or other data, please contact us.

• All specifications are subject to change without notice.

Ceramic Capacitors

Disk with Metal Fitting Type Electrode
Ultra High Voltage

UHV and FHV Series

ELECTRICAL CHARACTERISTICS/DIMENSIONS

TYPICAL CAPACITANCE CHARACTERISTICS

UHV SERIES(DC. 20 to 50kV, TC:Z5T)

Rated voltage Edc(kV)	Part No.	Rated capacitance (pF)±10%	Dimensions (mm)			Female thread
			øD	T	L	
20	UHV-221A	200	20	19	23	ISO M4
	UHV-222A	400	25			
	UHV-223A	700	30			
	UHV-224A	1,000	34			ISO M5
	UHV-1A	1,400	38			
	UHV-2A	2,500	48			
30	UHV-3A	4,000	60	22	26	ISO M4
	UHV-231A	200	25			
	UHV-232A	400	30			
	UHV-233A	700	34			ISO M5
	UHV-4A	940	38			
	UHV-5A	1,700	48			
40	UHV-6A	2,700	60	28	32	ISO M4
	UHV-241A	100	20			
	UHV-242A	200	25			
	UHV-243A	400	34			ISO M5
	UHV-7A	700	38			
	UHV-8A	1,300	48			
50	UHV-9A	2,000	60	31	35	ISO M4
	UHV-251A	100	20			
	UHV-252A	200	30			
	UHV-253A	400	34			ISO M5
	UHV-10A	560	38			
	UHV-11A	1,000	48			
	UHV-12A	1,700	60			


FHV SERIES(DC. 15 to 50kV, TC:Y5S)

Rated voltage Edc(kV)	Part No.	Rated capacitance (pF)±10%	Dimensions (mm)			Female thread
			øD	T	L	
15	FHV-153AN	7,000	60	17	21	ISO M5
	FHV-1AN	1,700	38			
20	FHV-2AN	3,000	48	18.5	22.5	ISO M5
	FHV-3AN	5,200	60			
	FHV-4AN	1,200	38			
30	FHV-5AN	2,100	48	22	26	ISO M5
	FHV-6AN	3,500	60			
	FHV-7AN	850	38			
40	FHV-8AN	1,500	48	26	30	ISO M5
	FHV-9AN	2,600	60			
	FHV-10AN	700	38			
50	FHV-11AN	1,300	48	29	33	ISO M5
	FHV-12AN	2,100	60			


TYPICAL CAPACITANCE CHARACTERISTICS

CAPACITANCE vs. TEMPERATURE CHARACTERISTICS

UHV SERIES(DC. 20 to 50kV, TC:Z5T)



FHV SERIES(DC. 15 to 50kV, TC:Y5S)



• For more information about products with other capacitance or other data, please contact us.

• All specifications are subject to change without notice.


Ceramic Capacitors

UHV and FHV Series


Disk with Metal Fitting Type Electrode
Ultra High Voltage

CAPACITANCE vs. DC BIAS CHARACTERISTICS

UHV SERIES(DC: 20 to 50kV, TC:Z5T)



FHV SERIES(DC: 15 to 50kV, TC:Y5S)



PRECAUTIONS

(1) During transportation and storage

- Do not transport or store where the capacitor will be exposed to high temperature or high humidity.
- Do not expose to poisonous gases such as H₂SO₄, HCl, or HNO₃.
- Avoid excessive impact such as that caused by falling.

(2) During operation

- Avoid contact with electrolytes such as perspiration. Do not touch with bare hands.
- Avoid excessive impact such as that caused by falling.
- Do not apply solder to stud terminals.
- Do not re-machine the terminals.

(3) Usage

- When the capacitor is used for high-speed pulses such as with a laser, make sure that the impressed voltage (peak-to-peak voltage) is within the capacitor's rated specifications.
- Make sure that the capacitor is not exposed to radiant heat from chambers or transformers.

• For more information about products with other capacitance or other data, please contact us.

• All specifications are subject to change without notice.