

Rail-to-rail input/output 20MHz GBP operational amplifiers

Features

- Low input offset voltage: 1.5mV max
- Rail-to-rail input and output
- Wide bandwidth 20MHz, stable for gain ≥ 3
- Low power consumption: 1.1mA maximum
- High output current: 35mA
- Operating from 2.5V to 5.5V
- Low input bias current, 1pA typ
- ESD internal protection ≥ 5 kV
- Latch-up immunity

Description


The TSV991/2/4 family of single, dual & quad operational amplifiers offers low voltage operation and rail-to-rail input and output.

This family features an excellent speed/power consumption ratio, offering a 20MHz gain-bandwidth, stable for gain above 3 (100pF capacitive load), while consuming only 1.1mA max at 5V supply voltage. It also features an ultra-low input bias current.

These characteristics make the TSV991/2/4 family ideal for sensor interfaces, battery-supplied and portable applications, as well as active filtering.

Applications

- Battery-powered applications
- Portable devices
- Signal conditioning
- Active filtering
- Medical instrumentation



Contents

1	Absolute maximum ratings & operating conditions	3
2	Electrical characteristics	5
3	Package information	11
4	Ordering information	16
5	Revision history	17

1 Absolute maximum ratings & operating conditions

Table 1. Absolute maximum ratings (AMR)

Symbol	Parameter	Value	Unit
V_{CC}	Supply voltage ⁽¹⁾	6	V
V_{id}	Differential input voltage ⁽²⁾	$\pm V_{CC}$	V
V_{in}	Input voltage ⁽³⁾	$V_{DD}-0.2$ to $V_{CC}+0.2$	V
T_{stg}	Storage temperature	-65 to +150	°C
R_{thja}	Thermal resistance junction to ambient ^{(4) (5)}		°C/W
	SOT23-5	250	
	SO-8	125	
	MiniSO-8	190	
	SO-14	103	
	TSSOP14	100	
R_{thjc}	Thermal resistance junction to case		°C/W
	SOT23-5	81	
	SO-8	40	
	MiniSO8	39	
	SO14	31	
	TSSOP14	32	
T_j	Maximum junction temperature	150	°C
ESD	HBM: human body model ⁽⁶⁾	5	kV
	MM: machine model ⁽⁷⁾	400	V
	CDM: charged device model ⁽⁸⁾ SOT23-5, SO-8, MSO8, SO14 TSSOP14	1500	V
		750	
	Latch-up immunity	200	mA

1. Value with respect to V_{DD} pin.
2. Differential voltages are the non-inverting input terminal with respect to the inverting input terminal.
3. $V_{CC}-V_{in}$ must not exceed 6V.
4. Short-circuits can cause excessive heating and destructive dissipation.
5. R_{th} are typical values.
6. Human body model: 100pF discharged through a 1.5k Ω resistor between two pins of the device, done for all couples of pin combinations with other pins floating.
7. Machine model: 200pF is charged to the specified voltage, then discharged directly between two pins of the device with no external series resistor (internal resistor < 5 Ω), done for all couples of pin combinations with other pins floating.
8. Charged device model: all pins plus package are charged together to the specified voltage and then discharged directly to the ground.

Table 2. Operating conditions

Symbol	Parameter	Value	Unit
V_{CC}	Supply voltage	2.5 to 5.5	V
V_{icm}	Common mode input voltage range	$V_{DD} - 0.1$ to $V_{CC} + 0.1$	V
T_{oper}	Operating free air temperature range	-40 to +125	°C

2 Electrical characteristics

Table 3. Electrical characteristics at $V_{CC} = +2.5V$, $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, $T_{amb} = 25^{\circ}C$, R_L connected to $V_{CC}/2$ (unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
DC performance						
V_{io}	Offset voltage TSV99x	$T_{min} < T_{op} < T_{max}$	-	0.1	4.5	mV
			-	-	7.5	
	TSV99xA	$T_{min} < T_{op} < T_{max}$	-	-	1.5	
			-	-	3	
DV_{io}	Input offset voltage drift		-	2	-	$\mu V/^{\circ}C$
I_{io}	Input offset current ⁽¹⁾ ($V_{out} = V_{CC}/2$)		-	1	10	pA
I_{ib}	Input bias current ⁽¹⁾ ($V_{out} = V_{CC}/2$)		-	1	10	pA
CMR	Common mode rejection ratio $20 \log(\Delta V_{ic}/\Delta V_{io})$	$0V$ to $2.5V$, $V_{out} = 1.25V$	58	75	-	dB
A_{vd}	Large signal voltage gain	$R_L = 10k\Omega$, $V_{out} = 0.5V$ to $2V$	80	89	-	dB
$V_{CC}-V_{OH}$	High level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$		15 45	40 150	mV
V_{OL}	Low level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$	-	15 45	40 150	mV
I_{out}	I_{sink}	$V_o = 2.5V$	18	32	-	mA
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
	I_{source}	$V_o = 0V$	18	35	-	
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
I_{CC}	Supply current (per operator)	No load, $V_{out} = V_{CC}/2$	-	0.78	1.1	mA
		$T_{min} < T_{op} < T_{max}$	-	-	1.1	
AC performance						
GBP	Gain bandwidth product	$R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$	-	20	-	MHz
ϕ_m	Phase margin	$R_L = 2k\Omega$, $C_L = 100pF$, $G=5$, $f=100kHz$	-	60	-	Degrees
G_m	Gain margin	$R_L = 2k\Omega$, $C_L = 100pF$, $\phi_m=40^{\circ}$	-	2.5	-	dB
SR	Slew rate	$R_L = 2k\Omega$, $C_L = 100pF$	-	10	-	V/ μs
e_n	Equivalent input noise voltage	$f=10kHz$	-	21	-	$\frac{nV}{\sqrt{Hz}}$
THD+ e_n	Total harmonic distortion	$G=1$, $f=1kHz$, $R_I=2k\Omega$, $BW=22kHz$, $V_{icm}=(V_{cc}+1)/2$, $V_{out}=1.1V_{pp}$	-	0.0017	-	%

1. Guaranteed by design.

Table 4. Electrical characteristics at $V_{CC} = +3.3V$, $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, $T_{amb} = 25^{\circ}C$, R_L connected to $V_{CC}/2$ (unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
DC performance						
V_{io}	Offset voltage TSV99x		-	0.1	4.5	mV
		$T_{min} < T_{op} < T_{max}$	-	-	7.5	
	TSV99xA		-	-	1.5	
		$T_{min} < T_{op} < T_{max}$	-	-	3	
DV_{io}	Input offset voltage drift		-	2	-	$\mu V/^{\circ}C$
I_{io}	Input offset current ⁽¹⁾		-	1	10	pA
I_{ib}	Input bias current ⁽¹⁾		-	1	10	pA
CMR	Common mode rejection ratio $20 \log (\Delta V_{ic}/\Delta V_{io})$	$0V$ to $3.3V$, $V_{out} = 1.65V$	60	78	-	dB
A_{vd}	Large signal voltage gain	$R_L=10k\Omega$, $V_{out}= 0.5V$ to $2.8V$	80	90	-	dB
$V_{CC}-V_{OH}$	High level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$		15 45	40 150	mV
V_{OL}	Low level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$	-	15 45	40 150	mV
I_{out}	I_{sink}	$V_o = 3.3V$	18	32	-	mA
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
	I_{source}	$V_o = 0V$	18	35	-	
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
I_{CC}	Supply current (per operator)	No load, $V_{out}=V_{CC}/2$	-	0.8	1.1	mA
		$T_{min} < T_{op} < T_{max}$	-	-	1.1	
AC performance						
GBP	Gain bandwidth product	$R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$	-	20	-	MHz
ϕ_m	Phase margin	$R_L = 2k\Omega$, $C_L = 100pF$, $G=5$	-	60	-	Degrees
G_m	Gain margin	$R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$, $\phi_m=40^{\circ}$	-	2.5	-	dB
SR	Slew rate	$R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$	-	10	-	V/ μs
e_n	Equivalent input noise voltage	$f=10kHz$	-	21	-	$\frac{nV}{\sqrt{Hz}}$
THD+ e_n	Total harmonic distortion	$G=1$, $f=1kHz$, $R_L=2k\Omega$, $BW=22kHz$, $V_{icm}=(V_{cc}+1)/2$, $V_{out}=1.9V_{pp}$	-	0.001	-	%

1. Guaranteed by design.

Table 5. Electrical characteristics at $V_{CC} = +5V$, $V_{DD} = 0V$, $V_{icm} = V_{CC}/2$, $T_{amb} = 25^{\circ}C$, R_L connected to $V_{CC}/2$ (unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
DC performance						
V_{io}	Offset voltage TSV99x		-	0.1	4.5	mV
		$T_{min} < T_{op} < T_{max}$	-	-	7.5	
	TSV99xA		-	-	1.5	
		$T_{min} < T_{op} < T_{max}$	-	-	3	
DV_{io}	Input offset voltage drift		-	2	-	$\mu V/^{\circ}C$
I_{io}	Input offset current ⁽¹⁾		-	1	10	pA
I_{ib}	Input bias current ⁽¹⁾		-	1	10	pA
CMR	Common mode rejection ratio $20 \log (\Delta V_{ic}/\Delta V_{io})$	0V to 5V, $V_{out} = 2.5V$	62	82	-	dB
SVR	Supply voltage rejection ratio $20 \log (\Delta V_{CC}/\Delta V_{io})$	$V_{CC} = 2.5$ to 5V	70	86	-	dB
A_{vd}	Large signal voltage gain	$R_L=10k\Omega$, $V_{out}= 0.5V$ to 4.5V	80	91	-	dB
$V_{CC}-V_{OH}$	High level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$		15 45	40 150	mV
V_{OL}	Low level output voltage	$R_L = 10k\Omega$ $R_L = 600\Omega$	-	15 45	40 150	mV
I_{out}	I_{sink}	$V_o = 5V$	18	32	-	mA
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
	I_{source}	$V_o = 0V$	18	35	-	
		$T_{min} < T_{amb} < T_{max}$	16	-	-	
I_{CC}	Supply current (per operator)	No load, $V_{out}=2.5V$	-	0.82	1.1	mA
		$T_{min} < T_{op} < T_{max}$	-	-	1.1	
AC performance						
GBP	Gain bandwidth product	$R_L = 2k\Omega$, $C_L = 100pF$, $f = 100kHz$	-	20	-	MHz
ϕ_m	Phase margin	$R_L = 2k\Omega$, $C_L = 100pF$, $G=5$	-	60	-	Degrees
G_m	Gain margin	$R_L = 2k\Omega$, $C_L=100pF$, $\phi_m=40^{\circ}$	-	2.5	-	dB
SR	Slew rate	$R_L = 2k\Omega$, $C_L = 100pF$	-	10	-	V/ μs
e_n	Equivalent input noise voltage	$f=10kHz$	-	21	-	$\frac{nV}{\sqrt{Hz}}$
THD+ e_n	Total harmonic distortion	$G=1$, $f=1kHz$, $R_I=2k\Omega$, $BW=22kHz$, $V_{icm}=(V_{CC}+1)/2$, $V_{out}=3.6V_{pp}$	-	0.0007	-	%

1. Guaranteed by design.

Figure 1. Input offset voltage distribution at T=25°C




Figure 2. Input offset voltage distribution at T=125°C




Figure 3. Supply current vs. input common mode voltage at V_{CC}=2.5V




Figure 4. Supply current vs. input common mode voltage at V_{CC}=5V




Figure 5. Output current vs. output voltage at V_{CC}=2.5V




Figure 6. Output current vs. output voltage at V_{CC}=5V




Figure 7. Voltage gain and phase vs frequency at $V_{CC}=5V$ and $V_{icm}=0.5V$




Figure 8. Voltage gain and phase vs frequency at $V_{CC}=5V$ and $V_{icm}=2.5V$




Figure 9. Positive slew rate




Figure 10. Negative slew rate




Figure 11. Distortion + noise vs. frequency




Figure 12. Distortion + noise vs. output voltage





Figure 13. Noise vs. frequency



3 Package information

In order to meet environmental requirements, STMicroelectronics offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an STMicroelectronics trademark. ECOPACK specifications are available at: www.st.com.

Figure 14. SOT23-5 package




Figure 15. MiniSO-8 package

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.1			0.043
A1	0.05	0.10	0.15	0.002	0.004	0.006
A2	0.78	0.86	0.94	0.031	0.034	0.037
b	0.25	0.33	0.40	0.010	0.013	0.016
c	0.13	0.18	0.23	0.005	0.007	0.009
D	2.90	3.00	3.10	0.114	0.118	0.122
E	4.75	4.90	5.05	0.187	0.193	0.199
E1	2.90	3.00	3.10	0.114	0.118	0.122
e		0.65			0.026	
K	0°		6°	0°		6°
L	0.40	0.55	0.70	0.016	0.022	0.028
L1			0.10			0.04




Figure 16. SO-8 package




Figure 17. TSSOP14 package

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.2			0.047
A1	0.05		0.15	0.002	0.004	0.006
A2	0.8	1	1.05	0.031	0.039	0.041
b	0.19		0.30	0.007		0.012
c	0.09		0.20	0.004		0.0089
D	4.9	5	5.1	0.193	0.197	0.201
E	6.2	6.4	6.6	0.244	0.252	0.260
E1	4.3	4.4	4.48	0.169	0.173	0.176
e		0.65 BSC			0.0256 BSC	
K	0°		8°	0°		8°
L1	0.45	0.60	0.75	0.018	0.024	0.030

Figure 18. SO-14 package

Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.75			0.068
a1	0.1		0.2	0.003		0.007
a2			1.65			0.064
b	0.35		0.46	0.013		0.018
b1	0.19		0.25	0.007		0.010
C		0.5			0.019	
c1	45° (typ.)					
D	8.55		8.75	0.336		0.344
E	5.8		6.2	0.228		0.244
e		1.27			0.050	
e3		7.62			0.300	
F	3.8		4.0	0.149		0.157
G	4.6		5.3	0.181		0.208
L	0.5		1.27	0.019		0.050
M			0.68			0.026
S	8° (max.)					

The figure contains three technical drawings of the SO-14 package:

- Side View (Left):** Shows the package profile with dimensions *a2*, *A*, *b*, *e3*, and *e*.
- Top View (Bottom):** Shows the package footprint with dimensions *D*, *M*, and *F*. Pin numbers 1, 7, 8, and 14 are indicated.
- Perspective View (Right):** Shows the package with dimensions *L*, *G*, *C*, *c1*, *a1*, *b1*, and *S*.

4 Ordering information

Part number	Temperature range	Package	Packing	Marking
TSV991ILT	-40°C to +125°C	SOT23-5	Tape & reel	K130
TSV991AILT				K129
TSV992IST		MiniSO-8		K132
TSV992AIST				K135
TSV992ID TSV992IDT		SO-8	Tube or tape & reel	V992I
TSV992AID TSV992AIDT				V992AI
TSV994IPT		TSSOP14	Tape & reel	V994I
TSV994AIPT				V994AI
TSV994ID TSV994IDT		SO-14	Tube or tape & reel	V994I
TSV994AID TSV994AIDT				V994AI

5 Revision history

Date	Revision	Changes
31-Jul-2006	1	Preliminary data release for product under development.
7-Nov-2006	2	Final version of datasheet.
12-Dec-2006	3	Noise and distortion figures added.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2006 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com