

RC2000C-S Series

Common Mode Reactor

Inquiry

Single phase 2 lines/Length mounted type



Application

Noise suppression for Switching power supply/Inverter

Specifications

RC2000C-SA Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	H	A
RC2003C-SA	250	3	1	70	25	20	27	10
RC2005C-SA		5	1	50	25	20	27	10
RC2010C-SA		10	1	30	37	25	35	18
RC2015C-SA		15	1	20	37	25	35	18
RC2000C-SB Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	H	A
RC2003C-SB	250	3	2	80	25	20	27	10
RC2005C-SB		5	2	70	25	20	27	10
RC2010C-SB		10	2	40	37	25	35	18
RC2000C-SC Series								
Parts No.	Rated Voltage [VAC]	Rated Current [A]	Inductance[mH typ]	Resistance[m ohm max]	Dimension [mm]			
					D	W	H	A
RC2003C-SC	250	3	3	100	25	20	27	10
RC2005C-SC		5	3	70	37	25	35	18
RD2000C-SD Series								
	Rated Voltage	Rated Current	Inductance[mH]	Resistance[m ohm]	Dimension [mm]			

Parts No.	[VAC]	[A]	typ]	max]	D	W	H	A
RD2005C-SD	250	5	5	80	37	25	35	18

Fig

