

Digital Indicator

Model No. ASI - 307



► Features

- Peak, Hold, Data Protection(Key Lock), Auto Zero : Front Key or External Signal Terminal Operation
- Sampling Speed Control (Max 20Hz)
- Auto Calibration, Offset Function
- Filtering : 10Hz, 100Hz, 1kHz, W/B (User Selectable)

► Performance Specs

DISPLAY:

- Range: -19999 to 99999
- Decimal Point : Selectable Position
- 5-digit Segment FND
- Sampling rate 5KHz

SENSOR INPUT:

- AC 0.5 ~ 3.5 mV/V (AC Strain Gauge Type)
- Excitation Voltage : AC 2Vrms
- Accuracy : $\pm 0.02\%$ of reading
- Impedance : 100 Mohm

POWER SUPPLY:

- AC supply voltage : 100, 220VAC, 50/60Hz, 15VA

ANALOG OUTPUT:

- DC 0 ~ $\pm 10V$, 0(4) ~ 20mA

DUAL LIMIT RELAYS

- Relay Mode : Hysteresis, Range Function

► Product Specification Chart

ASI - 307 - X X X

► Communications

- 0 = None
 - 1 = RS232
 - 2 = RS485
 - 3 = BCD
 - 4 = Binary
- } Option

► Relays

- 0 = Dual Relays (Option)
- 1 = Eight Relays (Option)

► Operating power

- 0 = AC Power
- 1 = DC Power (Option)

► Dimensions (mm)

