


MECHANICAL DATA

Dimensions in mm (inches)


**N-CHANNEL
POWER MOSFET
FOR HI-REL
APPLICATIONS**

V_{DSS}	200V
$I_{D(cont)}$	13A
$R_{DS(on)}$	0.18Ω

FEATURES

- HERMETICALLY SEALED TO-66 METAL PACKAGE
- SIMPLE DRIVE REQUIREMENTS
- SCREENING OPTIONS AVAILABLE

TO-66 METAL PACKAGE (TO213AA)
Underside View

Pin 1 = Gate Pin 2 = Source Case = Drain

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25^{\circ}C$ unless otherwise stated)

V_{GS}	Gate – Source Voltage	±20V
I_D	Continuous Drain Current @ $T_{case} = 25^{\circ}C$	13A
I_D	Continuous Drain Current @ $T_{case} = 100^{\circ}C$	8A
I_{DM}	Pulsed Drain Current	50A
P_D	Power Dissipation @ $T_{case} = 25^{\circ}C$	70W
	Linear Derating Factor	0.56W/°C
T_J, T_{stg}	Operating and Storage Temperature Range	-55 to 150°C
$R_{\theta JC}$	Thermal Resistance Junction to Case	1.8°C/W max.
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	50°C/W max.

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

ELECTRICAL CHARACTERISTICS ($T_C = 25^\circ\text{C}$ unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
STATIC ELECTRICAL RATINGS						
BV_{DSS}	Drain – Source Breakdown Voltage	$V_{GS} = 0$	$I_D = 250\mu\text{A}$	200	V	
$\frac{\Delta BV_{DSS}}{\Delta T_J}$	Temperature Coefficient of Breakdown Voltage	Reference to 25°C $I_D = 1\text{mA}$		1.42	$\text{V}/^\circ\text{C}$	
$R_{DS(on)}$	Static Drain – Source On–State Resistance	$V_{GS} = 10\text{V}$	$I_D = 7\text{A}^*$	0.14	0.18	Ω
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$	$I_D = 250\mu\text{A}$	2	4	V
g_{fs}	Forward Transconductance	$V_{DS} \geq I_D \times R_{DS(on)}$ $I_D = 7\text{A}^*$		6	9	$\text{S}(\bar{v})$
I_{DSS}	Zero Gate Voltage Drain Current	$V_{GS} = 0$	$V_{DS} = 0.8BV_{DSS}$ $T_J = 125^\circ\text{C}$		250 1000	μA
I_{GSS}	Forward Gate – Source Leakage	$V_{GS} = 20\text{V}$			100	nA
I_{GSS}	Reverse Gate – Source Leakage	$V_{GS} = -20\text{V}$			-100	
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	$V_{GS} = 0$		1275		pF
C_{oss}	Output Capacitance	$V_{DS} = 25\text{V}$		500		
C_{rss}	Reverse Transfer Capacitance	$f = 1\text{MHz}$		160		
Q_g	Total Gate Charge	$V_{GS} = 10\text{V}$ $I_D = 16\text{A}$		43	60	nC
Q_{gs}	Gate – Source Charge	$V_{DS} = 0.8BV_{DSS}$		16		
Q_{gd}	Gate – Drain (“Miller”) Charge			27		
$t_{d(on)}$	Turn–On Delay Time	$V_{DD} = 75\text{V}$		16	30	ns
t_r	Rise Time	$I_D = 7\text{A}$		27	60	
$t_{d(off)}$	Turn–Off Delay Time	$Z_0 = 4.7\Omega$		40	80	
t_f	Fall Time			31	60	
SOURCE – DRAIN DIODE CHARACTERISTICS						
I_S	Continuous Source Current				13	A
I_{SM}	Pulse Source Current				50	
V_{SD}	Diode Forward Voltage	$I_S = 13\text{A}$	$T_J = 25^\circ\text{C}$		2	V
		$V_{GS} = 0$				
t_{rr}	Reverse Recovery Time	$I_F = 13\text{A}$	$T_J = 25^\circ\text{C}$		650	ns
Q_{rr}	Reverse Recovery Charge	$d_i / d_t \leq 100\text{A}/\mu\text{s}$ $V_{DD} \leq 50\text{V}$			4.1	μC
PACKAGE CHARACTERISTICS						
L_D	Internal Drain Inductance	(from 6mm down drain lead pad to centre of die)		5.0		nH
L_S	Internal Source Inductance	(from 6mm down source lead to centre of source bond pad)		12.5		

* Pulse width $\leq 300\mu\text{s}$; Duty Cycle $\leq 2\%$

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.