

13 12 11 10 9 8 7 6 5 4 3 2 1

CHARACTERISTIC DESCRIPTION

ITEMS PRECEDED BY 'X' ARE NOT AVAILABLE

"X"	ITEM NO.	CKT. SIZE	TERMINAL VERSION REQUIRED AT EACH CIRCUIT LOCATION: *S* = STD. LENGTH *M* = MAKE-FIRST/BREAK-LAST * - * = VOIDED CIRCUIT																								DIM "D" REF.	DIM "E"	P.C. BOARD THICKNESS
			1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24			
X	44068-0230	04BA	4	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0231	06BA	6	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0232	08BA	8	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0233	10BA	10	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0234	12BA	12	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0235	14BA	14	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0236	16BA	16	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0237	18BA	18	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0238	20BA	20	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0239	22BA	22	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	5.21 (.205)	N / A	N / A	
X	44068-0240	24BA	24	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	5.21 (.205)	N / A	N / A	
	44068-0241	10BB	10	BM	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	5.21 (.205)	N / A	N / A	
	44068-0242	18BC	18	CS	CS	CM	CS	CS	CS	CM	CS	CS	CS	CS	CS	CM	CS	CS	CS	CS	CS	CS	CS	CS	CS	5.70 (.224)	4.19 (.165)	3.18 ± 0.18 (.125 ± .007)	
	44068-1000	14BB	14	BM	BM	BM	BM	BM	BS	BS	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	4.88 (.192)	4.19 (.165)	3.18 ± 0.18 (.125 ± .007)	
	44068-1001	18BC	18	CM	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	CS	-	-	-	-	-	6.60 (.260)	N / A	N / A	
	44068-1002	10BC	10	CS	CS	CS	CM	CM	CS	CS	CS	CS	CS	-	-	-	-	-	-	-	-	-	-	-	-	4.42 (.174)	3.40 (.134)	2.39 ± 0.18 (.094 ± .007)	
	44068-1003	18BB	18	BM	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	3.30 (.130)	2.59 (.102)	1.60 ± 0.18 (.063 ± .007)	
	44068-1004	14BB	14	BM	BS	BS	BS	BS	BS	BM	BM	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	BS	3.30 (.130)	2.59 (.102)	1.60 ± 0.18 (.063 ± .007)	
	44068-1005	10BB	10	BM	BM	BS	BM	BM	BM	BM	BM	BM	BM	-	-	-	-	-	-	-	-	-	-	-	-	4.88 (.192)	4.19 (.165)	3.18 ± 0.18 (.125 ± .007)	
	44068-1006	24BB	24	BM	BS	BM	BM	BM	BM	BM	BM	BM	BM	BS	BM	BS	BM	BM	BM	BM	BM	BM	BM	BM	BS	4.42 (.174)	3.40 (.134)	2.39 ± 0.18 (.094 ± .007)	
	44068-1007	14BB	14	BS	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BS	4.42 (.174)	3.40 (.134)	2.39 ± 0.18 (.094 ± .007)	
	44068-1008	18BB	18	BS	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BM	BS	4.42 (.174)	3.40 (.134)	2.39 ± 0.18 (.094 ± .007)	

CHARACTERISTICS LEGEND:

CIRCUIT SIZE _____ ** * *

(02-24)

HOUSING MAT'L. (SEE NOTE 1)

"B" = NYLON 4/6, U.L. 94V-0, COLOR: NATURAL (BLACK)

TERMINAL PLATING (SEE NOTE 6)

"A" = 200 M.I. TIN
 "B" = 30 M.I. GOLD
 "C" = 100 M.I. TIN

SEE SHEET 1 FCC NO: UCP2007-0614 DRAWING: STEWART 2006/09/08 CHKD: GPOLGAR 2006/09/08 APPR: ICOMERCI 2006/09/11	QUALITY SYMBOLS 	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
				MM/IN		1:1	METRIC	
		4 PLACES ± .010	± .010	DRAWN BY	DATE	TITLE		
		3 PLACES ± .025	± .014	MOSLEY	07/07/99	MINI-FIT JR BMI SMC VERTICAL HEADER ASSY MAKE-FIRST/BREAK-LAST		
2 PLACES ± 0.35	± .014	CHECKED BY	DATE	MATERIAL NO.		MOLEX INCORPORATED	DOCUMENT NO.	SHEET NO.
1 PLACE ± 0.35	± .014	BANDURA	07/07/99	SD-44068-051				
ANGULAR ± 1/2°		APPROVED BY	DATE	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
		EDGLEY	07/07/99	SIZE				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART						

12 11 10 9 8 7 6 5 4 3 2 1