



NOTES:

1. FOR USE WITH BOEING BMS13-65 OK & ADAMS RUSSELL FC48Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2229.
4. CENTER CONTACT, 1-7443-1MA9, SUPPLIED UNASSEMBLED.
5. INTERFACE PER MIL-STD-348, FIG. 317-1.
6. MARK PACKAGE: KINGS 845-9-9 (DATA CODE).
7. MATERIALS:
  - INSULATOR: TEFLON, ASTM D1710
  - GASKET: SIL. RUB., A-A-59588
  - C-RING: PHOS. BRONZE, ASTM B103
  - K-GRIP SLEEVE: COM. BRONZE, ALLOY ASTM B135
  - OUTER CONTACT: BER. COP., ASTM B196
  - ALL OTHER METAL PARTS: BRASS, ASTM B16
8. FINISHES:
  - CENTER CONTACT: .000050 MIN GOLD PLATE PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290 (RoHS)
  - OUTER CONTACT: .000200 MIN SILVER PER ASTM B700 OVER .000020 MIN COPPER PER ASTM B734 (RoHS)
  - ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
9. ELECTRICAL CHARACTERISTICS:
  - NOMINAL IMPEDANCE: 50 OHMS
  - WORKING VOLTAGE: 1500 VRMS
  - FREQUENCY RANGE: DC TO 4 GHz
10. WEIGHT: 56.5 GRAM

MARK: KINGS 845-9-9 (DATE CODE)

REVISIONS	
ISSUE	CHANGES
0	ER 35985 ME 12/12/94
1	ER 38568 E TEL 05/21/02
C	REVISED PER ER22996 GGR 03/29/2010
D	REVISED PER DMF304 & ER35797 TZ 11/17/11

845-9-9

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

PLUG, HN

DRAWN	MJB	DATE	08/09/94
DESIGN	CT	DATE	08/09/94
APPR.		DATE	

**KINGS**  
by WINCHESTER ELECTRONICS  
Winchester Electronics  
62 Barnes Industrial  
Road North  
Wallingford, CT 06492

845-9-9