



NOTES:

1. LOOSENING THUMBSCREW ALLOWS LENGTH ADJUSTMENT WITHOUT DISCONNECTING CABLE.

FREQ. (GHz)	VSWR (MAX.)	MIN. PHASE ADJUST	I.L. dB (MAX.)	MODEL #
DC - 2.3	1.35	15°/GHz	0.2	P2913
DC - 4.3	1.4	15°/GHz	0.3	P2914
DC - 8.2	1.5	15°/GHz	0.5	P2915
DC - 12.7	1.6	15°/GHz	0.5	P2916
DC - 18.0	1.7	15°/GHz	0.7	P2917

MATERIAL	TREATMENT	DRAWN	R. LYNCH	DATE	5/18/04		
FINISH	BRIGHT NICKEL	MOD NO.	P291_	CHECKED	DATE		
OUTLINE, P291_ LINE STRETCHER				APPROVED	DATE		
				CAGE CODE: OR8N4	DO NOT SCALE DWG		
ADVANCED TECHNICAL MATERIALS, INC. 49 RIDER AVE., PATCHOGUE N.Y. 11772 TEL: (631) 289-0363 FAX: (631) 289-0358 http://www.atmmicrowave.com		UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES TOLERANCES ARE:		FRACTIONS ±1/64	DECIMALS ±.01	ANGLES ±1/2°	SHEET. 1/1
		PROPRIETARY NOTICE: THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT THE PRIOR WRITTEN CONSENT OF ATM, INC.		SCALE 1 : 1	DWG. NO. 3934	REV. A	