


## General Description


The AO4610 uses advanced trench technology MOSFETs to provide excellent  $R_{DS(ON)}$  and low gate charge. The complementary MOSFETs may be used in inverter and other applications. A Schottky diode is co-packaged with the n-channel FET to minimize body diode losses. *Standard Product AO4610 is Pb-free (meets ROHS & Sony 259 specifications). AO4610L is a Green Product ordering option. AO4610 and AO4610L are electrically identical*

## Features


n-channel	p-channel
$V_{DS} (V) = 30V$	-30V
$I_D = 8.5A (V_{GS}=10V)$	-7.1A ( $V_{GS} = -10V$ )
$R_{DS(ON)}$	$R_{DS(ON)}$
< 18m $\Omega$ ( $V_{GS}=10V$ )	< 25m $\Omega$ ( $V_{GS} = -10V$ )
< 28m $\Omega$ ( $V_{GS}=4.5V$ )	< 40m $\Omega$ ( $V_{GS} = -4.5V$ )
$V_F < 0.5V @ 1A$	



SOIC-8



n-channel



p-channel

### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage	$V_{DS}$	30	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	$\pm 20$	V
Continuous Drain Current <sup>A</sup>	$I_D$	$T_A=25^\circ C$	8.5	A
		$T_A=70^\circ C$	6.6	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	30	-30	
Power Dissipation	$P_D$	$T_A=25^\circ C$	2	W
		$T_A=70^\circ C$	1.28	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	-55 to 150	$^\circ C$

Parameter	Symbol	Maximum Schottky	Units
Reverse Voltage	$V_{DS}$	30	V
Continuous Forward Current <sup>A</sup>	$I_D$	$T_A=25^\circ C$	A
		$T_A=70^\circ C$	
Pulsed Forward Current <sup>B</sup>	$I_{DM}$	20	
Power Dissipation <sup>A</sup>	$P_D$	$T_A=25^\circ C$	W
		$T_A=70^\circ C$	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	$^\circ C$

Thermal Characteristics: n-channel, Schottky and p-channel						
Parameter		Symbol	Device	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	t ≤ 10s	R <sub>θJA</sub>	n-ch	48	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		n-ch	74	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	R <sub>θJL</sub>	n-ch	35	60	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	t ≤ 10s	R <sub>θJA</sub>	p-ch	48	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		p-ch	74	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	R <sub>θJL</sub>	p-ch	35	40	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	t ≤ 10s	R <sub>θJA</sub>	Schottky	47.5	62.5	°C/W
Maximum Junction-to-Ambient <sup>A</sup>	Steady-State		Schottky	71	110	°C/W
Maximum Junction-to-Lead <sup>C</sup>	Steady-State	R <sub>θJL</sub>	Schottky	32	40	°C/W

N-Channel + Schottky Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	I <sub>D</sub> =250μA, V <sub>GS</sub> =0V	30			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =24V, V <sub>GS</sub> =0V T <sub>J</sub> =55°C			25	μA
I <sub>GSS</sub>	Gate-Body leakage current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1	1.8	3	V
I <sub>D(ON)</sub>	On state drain current	V <sub>GS</sub> =4.5V, V <sub>DS</sub> =5V	40			A
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =10V, I <sub>D</sub> =8.5A T <sub>J</sub> =125°C		15.5	18	mΩ
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =6.6A		22.3	27	mΩ
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =5V, I <sub>D</sub> =8.5A	10	23		S
V <sub>SD</sub>	Body-Diode+Schottky Forward Voltage	I <sub>S</sub> =1A		0.75	1	V
I <sub>S</sub>	Maximum Body-Diode+Schottky Continuous Current				5.5	A
<b>DYNAMIC PARAMETERS</b>						
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =15V, f=1MHz		1040		pF
C <sub>oss</sub>	Output Capacitance (FET+Schottky)			180		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			110		pF
R <sub>g</sub>	Gate resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz		0.7		Ω
<b>SWITCHING PARAMETERS</b>						
Q <sub>g(10V)</sub>	Total Gate Charge	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, I <sub>D</sub> =8.5A		19.2		nC
Q <sub>g(4.5V)</sub>	Total Gate Charge			9.36		nC
Q <sub>gs</sub>	Gate Source Charge			2.6		nC
Q <sub>gd</sub>	Gate Drain Charge			4.2		nC
t <sub>D(on)</sub>	Turn-On Delay Time	V <sub>GS</sub> =10V, V <sub>DS</sub> =15V, R <sub>L</sub> =1.8Ω, R <sub>GEN</sub> =3Ω		5.2		ns
t <sub>r</sub>	Turn-On Rise Time			4.4		ns
t <sub>D(off)</sub>	Turn-Off Delay Time			17.3		ns
t <sub>f</sub>	Turn-Off Fall Time			3.3		ns
t <sub>rr</sub>	Body-Diode+Schottky Reverse Recovery Time	I <sub>F</sub> =8.5A, di/dt=100A/μs		16.7		ns
Q <sub>rr</sub>	Body-Diode+Schottky Reverse Recovery Charge	I <sub>F</sub> =8.5A, di/dt=100A/μs		6.7		nC
<b>SCHOTTKY PARAMETERS</b>						
V <sub>F</sub>	Forward Voltage Drop	I <sub>F</sub> =1.0A		0.45	0.5	V
I <sub>rm</sub>	Maximum reverse leakage current	V <sub>R</sub> =30V		0.007	0.05	mA
		V <sub>R</sub> =30V, T <sub>J</sub> =125°C		3.2	10	
		V <sub>R</sub> =30V, T <sub>J</sub> =150°C		12	20	
C <sub>T</sub>	Junction Capacitance	V <sub>R</sub> =15V		37		pF

A: The value of R<sub>θJA</sub> is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The R<sub>θJA</sub> is the sum of the thermal impedance from junction to lead R<sub>θJL</sub> and lead to ambient.

D: The static characteristics in Figures 1 to 6 are obtained using 80 μs pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25°C. The SOA curve provides a single pulse rating.

Rev 4: July 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

N-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

N-CHANNEL: TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

P-Channel Electrical Characteristics (T<sub>J</sub>=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	I <sub>D</sub> =-250μA, V <sub>GS</sub> =0V	-30			V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =-24V, V <sub>GS</sub> =0V T <sub>J</sub> =55°C			-1 -5	μA
I <sub>GSS</sub>	Gate-Body leakage current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V			±100	nA
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250μA	-1.4	-2	-2.7	V
I <sub>D(ON)</sub>	On state drain current	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-5V	-30			A
R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =-10V, I <sub>D</sub> =-7.1A T <sub>J</sub> =125°C V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-5.6A		20 27 29	25 33 40	mΩ
g <sub>FS</sub>	Forward Transconductance	V <sub>DS</sub> =-5V, I <sub>D</sub> =-7.1A		19.6		S
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =-1A, V <sub>GS</sub> =0V		-0.7	-1	V
I <sub>S</sub>	Maximum Body-Diode Continuous Current				-4.2	A
<b>DYNAMIC PARAMETERS</b>						
C <sub>iss</sub>	Input Capacitance	V <sub>GS</sub> =0V, V <sub>DS</sub> =-15V, f=1MHz		1573		pF
C <sub>oss</sub>	Output Capacitance			319		pF
C <sub>rss</sub>	Reverse Transfer Capacitance			211		pF
R <sub>g</sub>	Gate resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, f=1MHz		6.7		Ω
<b>SWITCHING PARAMETERS</b>						
Q <sub>g</sub> (10V)	Total Gate Charge (10V)	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, I <sub>D</sub> =-7.1A		30.9		nC
Q <sub>g</sub> (4.5V)	Total Gate Charge (4.5V)			16.1		nC
Q <sub>gs</sub>	Gate Source Charge			8		nC
Q <sub>gd</sub>	Gate Drain Charge			4.4		nC
t <sub>D(on)</sub>	Turn-On DelayTime	V <sub>GS</sub> =-10V, V <sub>DS</sub> =-15V, R <sub>L</sub> =2.2Ω, R <sub>GEN</sub> =3Ω		9.5		ns
t <sub>r</sub>	Turn-On Rise Time			8		ns
t <sub>D(off)</sub>	Turn-Off DelayTime			44.2		ns
t <sub>f</sub>	Turn-Off Fall Time			22.2		ns
t <sub>rr</sub>	Body Diode Reverse Recovery Time	I <sub>F</sub> =-7.1A, di/dt=100A/μs		25.5		ns
Q <sub>rr</sub>	Body Diode Reverse Recovery Charge	I <sub>F</sub> =-7.1A, di/dt=100A/μs		14.7		nC

A: The value of R<sub>θJA</sub> is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25°C. The value in any given application depends on the user's specific board design. The current rating is based on the t ≤ 10s thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C: The R<sub>θJA</sub> is the sum of the thermal impedance from junction to lead R<sub>θJL</sub> and lead to ambient.

D: The static characteristics in Figures 1 to 6,12,14 are obtained using 80 μs pulses, duty cycle 0.5% max.

E: These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25°C. The SOA curve provides a single pulse rating.

Rev 4: July 2005

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Fig 16: On-Region Characteristics




Figure 17: Transfer Characteristics




Figure 18: On-Resistance vs. Drain Current and Gate Voltage




Figure 19: On-Resistance vs. Junction Temperature




Figure 20: On-Resistance vs. Gate-Source Voltage




Figure 21: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: P-CHANNEL




Figure 22: Gate-Charge Characteristics




Figure 23: Capacitance Characteristics




Figure 24: Maximum Forward Biased Safe Operating Area (Note E)




Figure 25: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 26: Normalized Maximum Transient Thermal Impedance



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS: SCHOTTKY




Figure 12: Schottky Forward Characteristics




Figure 13: Schottky Capacitance Characteristics




Figure 14: Schottky Forward Drop vs. Junction Temperature




Figure 15: Schottky Leakage current vs. Junction Temperature




Figure 15: Schottky Normalized Maximum Transient Thermal Impedance