


Data Sheet

Item	Contents		Criteria
1	Model	HCX-D095	10S- 10A working current-- 20A cut off
2	Voltage	Charging voltage	36 V
3	Current	Maximal continuous charging current	10A
		Maximal continuous discharging current	10A
		Current consumption	≤200 μ A
4	Overcharge Protection	Over charge detection voltage	3.9V±25mV
		Over charge detection delay time	1.2S
		Over charge release voltage	3.8V±25mV
5	Over Discharge Protection	Over discharge detection voltage	2.0V±50mV
		Over discharge detection delay time	144mS
		Over discharge release voltage	2.3V±50mV
6	Over Current Protection	Over current detection voltage	0.1V±15mV
		Over current detection current	20A
		Detection delay time	9mS
		Release condition	Cut load,automatically recover
7	Short Circuit Protection	Detection condition	Exterior shot circuit
		Detection delay time	320 μ S
		Release condition	Cut load,automatically recover
8	Balance	Balance voltage for single cell	3.6V±25mV
		Balance current for single cell	72mA±10mA
9	Resistance	Inner resistance	≤20m Ω
10	Temperature	Operating temperature range	-40~+85℃
		Storage temperature range	-40~+125℃
11	Size (L*W*H)	115mm * 80mm * 1.6mm	



Remarks:

Charge, Discharge from same Port
P+ = Charge+ / Discharge+
P- = Charge- / Discharge-

*Note: Characteristics subject to change without notice.

Bestech Power Co., Ltd

3F, Bldg3, Fulian Industrial Park, Heping Industrial area, Jianhui Rd, Longhua, ShenZhen, China.

中国广东省深圳市龙华和平路和平工业区建辉路 82 号旭焕辉富联工业园 2 期 3 栋 3 楼。

Website: <http://www.bestechpower.com>

E-mail: sales@bestechpower.com