

# GSS9936

## N-CHANNEL ENHANCEMENT MODE POWER MOSFET

BV <sub>DSS</sub>	30V
R <sub>DS(ON)</sub>	50mΩ
I <sub>D</sub>	5A




### Description

The GSS9936 provide the designer with the best combination of fast switching, ruggedized device design, ultra low on-resistance and cost-effectiveness.

### Features

- \*DC-DC Application
- \*Dual N-channel Device

### Package Dimensions



REF.	Millimeter		REF.	Millimeter	
	Min.	Max.		Min.	Max.
A	5.80	6.20	M	0.10	0.25
B	4.80	5.00	H	0.35	0.49
C	3.80	4.00	L	1.35	1.75
D	0°	8°	J	0.375 REF.	
E	0.40	0.90	K	45°	
F	0.19	0.25	G	1.27 TYP.	

### Absolute Maximum Ratings

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V <sub>DS</sub>	30	V
Gate-Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current <sup>3</sup>	I <sub>D</sub> @TA=25°C	5	A
Continuous Drain Current <sup>3</sup>	I <sub>D</sub> @TA=70°C	4	A
Pulsed Drain Current <sup>1</sup>	I <sub>DM</sub>	40	A
Total Power Dissipation	P <sub>D</sub> @TA=25°C	2	W
Linear Derating Factor		0.016	W/°C
Operating Junction and Storage Temperature Range	T <sub>j</sub> , T <sub>stg</sub>	-55 ~ +150	°C

### Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-ambient <sup>3</sup> Max.	R <sub>thj-amb</sub>	62.5	°C/W

**Electrical Characteristics(T<sub>j</sub> = 25°C Unless otherwise specified)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	30	-	-	V	V <sub>GS</sub> =0, I <sub>D</sub> =250uA
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS} / \Delta T_j$	-	0.037	-	V/°C	Reference to 25°C, I <sub>D</sub> =1mA
Gate Threshold Voltage	V <sub>GS(th)</sub>	1.0	-	3.0	V	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA
Forward Transconductance	g <sub>fs</sub>	-	6	-	S	V <sub>DS</sub> =15V, I <sub>D</sub> =5A
Gate-Source Leakage Current	I <sub>GSS</sub>	-	-	±100	nA	V <sub>GS</sub> = ±20V
Drain-Source Leakage Current(T <sub>j</sub> =25°C)	I <sub>DSS</sub>	-	-	1	uA	V <sub>DS</sub> =30V, V <sub>GS</sub> =0
Drain-Source Leakage Current(T <sub>j</sub> =70°C)		-	-	25	uA	V <sub>DS</sub> =24V, V <sub>GS</sub> =0
Static Drain-Source On-Resistance <sup>2</sup>	R <sub>DS(ON)</sub>	-	-	50	mΩ	V <sub>GS</sub> =10V, I <sub>D</sub> =5A
		-	-	80		V <sub>GS</sub> =4.5V, I <sub>D</sub> =3.9A
Total Gate Charge <sup>2</sup>	Q <sub>g</sub>	-	6.1	-	nC	I <sub>D</sub> =5A V <sub>DS</sub> =15V V <sub>GS</sub> =5V
Gate-Source Charge	Q <sub>gs</sub>	-	1.4	-		
Gate-Drain ("Miller") Charge	Q <sub>gd</sub>	-	3.3	-		
Turn-on Delay Time <sup>2</sup>	T <sub>d(on)</sub>	-	6.7	-	ns	V <sub>DS</sub> =15V I <sub>D</sub> =1.5A V <sub>GS</sub> =10V R <sub>G</sub> =3.3Ω R <sub>D</sub> =10Ω
Rise Time	T <sub>r</sub>	-	6.4	-		
Turn-off Delay Time	T <sub>d(off)</sub>	-	22.1	-		
Fall Time	T <sub>f</sub>	-	2.1	-		
Input Capacitance	C <sub>iss</sub>	-	240	-	pF	V <sub>GS</sub> =0V V <sub>DS</sub> =25V f=1.0MHz
Output Capacitance	C <sub>oss</sub>	-	145	-		
Reverse Transfer Capacitance	C <sub>rss</sub>	-	55	-		

**Source-Drain Diode**


Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Forward On Voltage <sup>2</sup>	V <sub>SD</sub>	-	-	1.2	V	I <sub>S</sub> =1.7A, V <sub>GS</sub> =0V, T <sub>j</sub> =25°C
Continuous Source Current (Body Diode)	I <sub>S</sub>	-	-	1.67	A	V <sub>D</sub> =V <sub>G</sub> =0V, V <sub>S</sub> =1.2V

Notes: 1. Pulse width limited by Max. junction temperature.


2. Pulse width ≤ 300us, duty cycle ≤ 2%.

3. Surface mounted on 1 in<sup>2</sup> copper pad of FR4 board; 135°C/W when mounted on Min. copper pad.


## Characteristics Curve




**Fig 1. Typical Output Characteristics**




**Fig 2. Typical Output Characteristics**




**Fig 3. On-Resistance v.s. Gate Voltage**




**Fig 4. Normalized On-Resistance v.s. Junction Temperature**




**Fig 5. Maximum Drain Current v.s. Case Temperature**




**Fig 6. Type Power Dissipation**




**Fig 7. Maximum Safe Operating Area**




**Fig 8. Effective Transient Thermal Impedance**




**Fig 9. Gate Charge Characteristics**




**Fig 10. Typical Capacitance Characteristics**




**Fig 11. Forward Characteristics of Reverse Diode**




**Fig 12. Gate Threshold Voltage v.s. Junction Temperature**




**Fig 13. Switching Time Circuit**



**Fig 14. Switching Time Waveform**



**Fig 15. Gate Charge Circuit**



**Fig 16. Gate Charge Waveform**

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of GTM.
- GTM reserves the right to make changes to its products without notice.
- GTM semiconductor products are not warranted to be suitable for use in life-support Applications, or systems.
- GTM assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory:**

- **Taiwan:** No. 17-1 Tatung Rd. Fu Kou Hsin-Chu Industrial Park, Hsin-Chu, Taiwan, R. O. C.
- TEL : 886-3-597-7061 FAX : 886-3-597-9220, 597-0785
- **China:** (201203) No.255, Jang-Jiang Tsai-Lueng RD. , Pu-Dung-Hsin District, Shang-Hai City, China
- TEL : 86-21-5895-7671 ~ 4 FAX : 86-21-38950165