



791-10-9

NOTES:

1. FOR USE WITH BOEING BMS13-65 OH & ADAMS RUSSELL FC28Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2212
4. INTERFACE PER MIL-STD-348, FIG. 302-2.
5. FOR USE WITH .188 MAX. PANEL
6. CENTER CONTACT (1-842-30MA9) SUPPLIED UNASSEMBLED.
7. MARK PACKAGE: KINGS 791-10-9 (DATE CODE)
8. MATERIALS:
 INSULATOR-TEFLON, ASTM D1710
 K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM B135
 CENTER CONTACT-BER. COP., ASTM B196
 ALL OTHER METAL PARTS-BRASS, ASTM B16
9. FINISHES:
 CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER
 .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290
 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
10. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE-50 OHMS
 FREQUENCY RANGE-DC TO 11 GHZ
 WORKING VOLTAGE-1000 VRMS
11. WEIGHT: 26.9 GRAMS

REVISIONS	
ISSUE	CHANGES
0	ER 35799 KH 09/16/94
1	CN 36939 A KH 04/23/96
C	REVISED PER DMF304 & ER35452 KPL 10/19/11
CUSTOMER SALES DRAWING	
<small>THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.</small>	
SCALE	4:1
APPROX SURFACE AREA	
CAGE CODE:	91836
REF:	BOEING
JACK, PANEL, C	
DRAWN KH	DATE 04/28/94
DESIGN JT	DATE 04/29/94
APPR.	DATE
 <small>Winchester Electronics Corporation 62 Barnes Industrial Road North Wallingford, Connecticut 06492</small>	
791-10-9	