



## SPECIFICATIONS

FREQUENCY RANGE: 2 TO 4 GHz

ISOLATION: 18

LOSS (dB) MIN: 0.6

VSWR MAX: 1.30:1

FORWARD POWER: 10 WATT

REVERSE POWER: 10 WATT

INPUT CONNECTOR: N TYPE

OUTPUT CONNECTOR: N TYPE



**PASTERNAK ENTERPRISES, INC.**

P.O BOX 16759, IRVINE, CA 92623  
PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)

**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE8311**

DES. N FEMALE ISOLATOR, 2 - 4 GHz, 10W

REV. B

**FSCM NO. 53919**

CAD FILE 042508

SCALE N/A

SIZE A 127

**NOTES:**

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.
4. LENGTH TOLERANCE IS  $\pm 1.5\%$  OR  $\pm 3/8"$ , WHICHEVER IS GREATER.