



General ordering data

Order No.	9457780300
Part designation	SAIL-VSBD-M12G-3.0U
Version	Valve plugs, Straight plug - valve plug, BD, Socket
EAN	4008190316969
Qty.	1 pc(s).

Technical data

Ambient temperature, max.	80 °C
Ambient temperature, min.	-25 °C
Cable diameter, min	6 mm
Connection cross-section	0.75
Contact gap, valve plug	10 mm
Contact material	CuZn
Contact surface	tinned
Contact tube diameter	Miscellaneous
Core cross-section	0.75 mm ²
Material	PUR
Protection class	IP 67
Rated current	4 A
Rated voltage	24 V
Sheathing colour	grey
No. of poles	3
Version	Straight plug - valve plug
Cable length	3 m

Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-26-07-01
eClass 5.0	27-26-07-01
eClass 5.1	27-26-07-01

Similar products

Order No.	Part designation	Version
9457780030	SAIL-VSBD-M12G-0.3U	Valve plugs, Straight plug - valve plug, BD, Socket
9457780060	SAIL-VSBD-M12G-0.6U	Valve plugs, Straight plug - valve plug, BD, Socket
9457780090	SAIL-VSBD-M12G-0.9U	Valve plugs, Straight plug - valve plug, BD, Socket
9457780120	SAIL-VSBD-M12G-1,2U	Valve plugs, Straight plug - valve plug, BD, Socket
9457780150	SAIL-VSBD-M12G-1.5U	Valve plugs, Straight plug - valve plug, BD, Socket
9457781000	SAIL-VSBD-M12G-10U	Valve plugs, Straight plug - valve plug, BD, Socket
9457780500	SAIL-VSBD-M12G-5.0U	Valve plugs, Straight plug - valve plug, BD, Socket