




- Metal Insulation Sleeve
- Molded Insulator
- Internal Barrel Serrations
- Funnel Entry




Nylon Insulated Locking Fork Terminals

Catalog Number	Wire Range	Bolt Size (d2)		Dimension <small>inch mm</small>						
				W	F	L	E	D	d1	T
KN18-6LF-M	22-16 A.W.G. 0.5-1.5 mm ²	#6	.146 3.7	.252 6.4	.256 6.5	.866 22.0	.433 11.0	.177 4.5	.067 1.7	.030 0.75
KN18-8LF-M		#8	.169 4.3	.283 7.2						
KN18-10LF-M		#10	.209 5.3	.319 8.1						
KN14-6LF-M	16-14 A.W.G. 1.5-2.5 mm ²	#6	.146 3.7	.236 6.0	.256 6.5	.866 22.0	.433 11.0	.205 5.2	.091 2.3	.031 0.8
KN14-8LF-M		#8	.169 4.3	.283 7.2						
KN14-10LF-M		#10	.209 5.3	.319 8.1						
KN10-6LF-D	12-10 A.W.G. 4-6 mm ²	#6	.146 3.7	.327 8.3	.276 7.0	.992 25.2	.512 13.0	.276 7.0	.134 3.4	.039 1.0
KN10-8LF-D		#8	.169 4.3	.327 8.3						
KN10-10LF-D		#10	.209 5.3	.354 9.0						

Box Quantity: (D)=500; (M)=1000
For Mylar Tape replace box quantity with (T). Example: KN18-6LF-T
UL File #E9809, CSA File #LR4503

See pages in back of catalog for complete tool information.
Tool and Die Selection Chart on page M42.

Maximum Electrical Rating: 105°C 600 Volts Max.
Terminal Material: Copper




Vinyl Insulated Locking Fork Terminals



M

Spec-Kon®

- Molded Funnel Entry Insulator
- Internal Barrel Serrations



Catalog Number	Wire Range	Bolt Size (d2)		Dimension <small>inch mm</small>						
				W	F	L	E	D	d1	T
KV18-6LF-M	22-16 A.W.G. 0.5-1.5 mm ²	#6	.146 3.7	.252 6.4	.256 6.5	.866 22.0	.433 11.0	.157 4.0	.067 1.7	.030 0.75
KV18-8LF-M		#8	.169 4.3	.283 7.2						
KV18-10LF-M		#10	.209 5.3	.319 8.1						
KV14-6LF-M	16-14 A.W.G. 1.5-2.5 mm ²	#6	.146 3.7	.236 6.0	.256 6.5	.866 22.0	.433 11.0	.177 4.5	.091 2.3	.031 0.8
KV14-8LF-M		#8	.169 4.3	.283 7.2						
KV14-10LF-M		#10	.209 5.3	.319 8.1						
KV10-6LF-D	12-10 A.W.G. 4-6 mm ²	#6	.146 3.7	.327 8.3	.276 7.0	.992 25.2	.512 13.0	.252 6.4	.134 3.4	.039 1.0
KV10-8LF-D		#8	.169 4.3	.327 8.3						
KV10-10LF-D		#10	.209 5.3	.354 9.0						

Box Quantity: (D)=500; (M)=1000
For Mylar Tape replace box quantity with (T).
Example: KV18-6LF-T
UL File #E9809, CSA File #LR4503

See pages in back of catalog for complete tool information.
Tool and Die Selection Chart on page M42.

Maximum Electrical Rating: 105°C 600 Volts Max.
Terminal Material: Copper

Tools used with Nylon and Vinyl Insulated Locking Fork Terminals

