

P-Channel Logic Level Enhancement Mode Power MOSFET

MTP4409H8

BV _{DSS}		-30V
I _D		-15A
R _{DSON(TYP)}	V _{GS} =-10V, I _D =-15A	7.3mΩ
	V _{GS} =-4.5V, I _D =-10A	11mΩ


Description

The MTP4409H8 is a P-channel enhancement-mode MOSFET, providing the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost effectiveness.


Features

- Single Drive Requirement
- Low On-resistance
- Fast Switching Characteristic
- Dynamic dv/dt rating
- Repetitive Avalanche Rated
- Pb-free lead plating and Halogen-free package

Symbol



Outline





Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit	
Drain-Source Voltage	V _{DS}	-30	V	
Gate-Source Voltage	V _{GS}	±20		
Continuous Drain Current @ T _C =25°C, V _{GS} =-10V	I _D	-63	A	
Continuous Drain Current @ T _C =100°C, V _{GS} =-10V		-40		
Continuous Drain Current @ T _A =25°C, V _{GS} =-10V	I _{DSM}	-15 *3		
Continuous Drain Current @ T _A =70°C, V _{GS} =-10V		-12 *3		
Pulsed Drain Current	I _{DM}	-200 *1,2		
Avalanche Current	I _{AS}	-15		
Avalanche Energy @ L=0.5mH, I _D =-15A, R _G =25 Ω	E _{AS}	56	mJ	
Total Power Dissipation	P _D	T _C =25°C	50	W
		T _C =100°C	20	
	P _{DSM}	T _A =25°C	2.5 *3	
		T _A =70°C	1.6 *3	
Operating Junction and Storage Temperature Range	T _j , T _{stg}	-55~+150	°C	

Thermal Data

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction-to-case, max	R _{th,j-c}	2.5	°C/W
Thermal Resistance, Junction-to-ambient, max	R _{th,j-a}	50 *3	°C/W

- Note : 1. Pulse width limited by maximum junction temperature.
 2. Duty cycle ≤ 1%.
 3. Surface mounted on 1 in² copper pad of FR-4 board; 125°C/W at minimum pad.

Characteristics (Tc=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	-30	-	-	V	V _{GS} =0, I _D =-250μA
V _{GS(th)}	-1	-1.5	-3.0	V	V _{DS} = V _{GS} , I _D =-250μA
G _{FS} *1	-	25	-	S	V _{DS} = -5V, I _D =-15A
I _{GSS}	-	-	±100	nA	V _{GS} =±20
I _{DSS}	-	-	-1	μA	V _{DS} = -30V, V _{GS} = 0
	-	-	-25		V _{DS} = -24V, V _{GS} = 0, T _j =125°C
R _{DS(ON)} *1	-	7.3	9.5	mΩ	V _{GS} = -10V, I _D =-15A
	-	11	17	mΩ	V _{GS} = -4.5V, I _D =-10A
Dynamic					
C _{iss}	-	4342	-	pF	V _{DS} =-25V, V _{GS} =0V, f=1MHz
C _{oss}	-	374	-		
C _{rss}	-	306	-		


Characteristics (Tc=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Qg *1, 2	-	78.3	-	nC	V _{DS} =-15V, V _{GS} =-10V, I _D =-15A
Qgs *1, 2	-	17.6	-		
Qgd *1, 2	-	18	-		
t _{d(ON)} *1, 2	-	27	-	ns	V _{DS} =-15V, I _D =-1A, V _{GS} =-10V, R _G =6Ω
tr *1, 2	-	18	-		
t _{d(OFF)} *1, 2	-	140	-		
tr *1, 2	-	50	-		
Source-Drain Diode					
I _S *1	-	-	-15	A	
I _{SM} *3	-	-	-60		
V _{SD} *1	-	-0.80	-1	V	I _S =-10A, V _{GS} =0V
trr	-	45	-	ns	I _F =-15A, dI _F /dt=100A/μs
Q _{rr}	-	38	-	nC	

Note : *1.Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%
 *2.Independent of operating temperature
 *3.Pulse width limited by maximum junction temperature.

Ordering Information


Device	Package	Shipping
MTP4409H8	DFN5×6 (Pb-free lead plating and halogen-free package)	3000 pcs / Tape & Reel

Recommended Soldering Footprint



unit : mm

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Reverse Drain Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics(Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Single Pulse Maximum Power Dissipation






Typical Characteristics(Cont.)


Typical Transfer Characteristics



Power Derating Curve




Transient Thermal Response Curves



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds


Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat		
-Temperature Min(T _{s min})	100°C	150°C
-Temperature Max(T _{s max})	150°C	200°C
-Time(t _{s min} to t _{s max})	60-120 seconds	60-180 seconds
Time maintained above:		
-Temperature (T _L)	183°C	217°C
- Time (t _L)	60-150 seconds	60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(t _p)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

DFN5x6 Dimension



DIM	Millimeters		Inches		DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039	k	1.190	1.390	0.047	0.055
A3	0.254	REF	0.010	REF	b	0.350	0.450	0.014	0.018
D	4.944	5.096	0.195	0.201	e	1.270	TYP.	0.050	TYP.
E	5.974	6.126	0.235	0.241	L	0.559	0.711	0.022	0.028
D1	3.910	4.110	0.154	0.162	L1	0.424	0.576	0.017	0.023
E1	3.375	3.575	0.133	0.141	H	0.574	0.726	0.023	0.029
D2	4.824	4.976	0.190	0.196	θ	10°	12°	10°	12°
E2	5.674	5.826	0.223	0.229					

Notes: 1.Controlling dimension: millimeters.
 2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.
 3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: Pure tin plated.
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.