

1										2										3										4										5										6										7										8																																																																															
ISS										ZONE										REVISIONS										DESCRIPTION\PER REQUEST\DATE																																																																																																																							
F										E										D										C										B										A										F										E										D										C										B										A																																							
																																																		<p>REMARK:1. NO.2 MUST WITHSTAND A 6 lbs. MIN. PUSHOUT FORCE FROM NO.1 AFTER STAKING OPERATION 2. REMARK1 IS MAINTAINED BY STAMPING THE FOUR POINTS SHOWN ON THE DRAWING WITHOUT PUNCTURING NO.1</p>																																																																																																			
<p>STAKE IN 4 PLACES EQUALLY SPACED 90° APART (SEE REMARK 1,2)</p>										<p>RECOMMENDED CABLE STRIPPING DIM'S</p>										<p>1. CRIMPED FERRULE HEX CRIMP SIZE .213" 2. CONTACT PIN TO SOLDER</p>																																																																																																																																	
<p>NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES) 1. BRASS PER QQ-B-626 2. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE 3. BERYLLIUM COPPER PER QQ-C-530 4. GOLD PL. 50 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE 5. TEFLON MIL-P-19468</p>										<p>SCALE 3/1</p>										<p>DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4</p>										<p>PART NO. SMA6111A4-3GT50G-5A-50</p>										<p>APPROVED DATE 10-11-01'</p>										<p>CHECKED DATE 10-11-01'</p>										<p>DRAWN DATE 10-11-01'</p>										<p>FILE NO.</p>																																																																															
<p>5 HEAT SHRINK TUBING</p>										<p>4 FERRULE</p>										<p>3 CONTACT PIN</p>										<p>2 INSULATOR</p>										<p>1 BODY</p>										<p>HT-56/5X193</p>										<p>FR-44/34X95C</p>										<p>SMA87051902-3</p>										<p>SMA87051902-2</p>										<p>SMA87110603-1</p>										<p>HT-56/5X193</p>										<p>FR-44/34X95C</p>										<p>SMA87051902-3</p>										<p>SMA87051902-2</p>										<p>SMA87110603-1</p>									
NO.										DESCRIPTION										MATERIAL										FINISH										Q'TY										DRAWING NO.										SCALE										3/1										ISSUE										A										FILE NO.										<p><b>Amphenol</b></p>										<p>TITLE SMA CRIMP JACK</p>										<p>DRAWING NO. KJ-SMA6111A4-3GT50G-316U/D-50</p>										<p>ITEM NO.</p>									
1										2										3										4										5										6										7										8																																																																															