



## TI1502SA-01 INVERTER ELECTRICAL SPECIFICATION

### 1. APPLICATION

This specification is applied to CCFL inverter unit for 18.5" 2L color LCD backlight.

Panel Type : CMO M185B1-L02 Rev.C1 & AUO M185XW01 V.0

& CMO M185B1-L03 Rev.C1 & CPT CLAA185WA02

Weight : 31g

### 2. ELECTRICAL CHARACTERISTICS

NO.	Item	Symbol	Condition	Min.	Typ.	Max.	Unit
1	Input Voltage	Vin		11	12	13	V
2	Input Current	Iin	Vin= 12 V, Vadj= 0 V ( 2 Lamp)	---	---	1.5	A
3	Inrush Current	Iin	Vin= 12 V, Vadj= -- V (Imax)	---	---	1.8	A
4	Input Power	Pin	Vin= 12 V, Vadj= 0 V ( 2 Lamp)	---	---	19.8	W
5	Backlight	Von	Normal Operation	2.4	---	5.0	V
	ON/OFF Control	Voff	Shutdown	0	---	1.2	V
6	Brightness Adjust (Lamp Current Control)	Vadj	Normal Operation	5	---	0	V
7	Output Voltage	Vout	Vin= 12 V, Iout= 7.0 mA ( 1 Lamp) (REF,VALUE)	---	775	---	Vrms
8	Output Current (Each Connector)	Iout(Min)	Vin= 12 V, Vadj= 5 V ( 1 Lamp) Ta= 25 °C, After running 30min.	2.0	2.5	3.0	mArms
		Iout(Max)	Vin= 12 V, Vadj= 0 V ( 1 Lamp) Ta= 25 °C, After running 30min.	6.5	7.0	7.5	mArms
9	Burst Frequency	Freq	Vin= --- V, Vadj= --- V	---	---	---	Hz
10	Frequency	Freq	Normal Operation	50	55	60	KHz
11	Lamp Start Voltage	Vopen	No Load, Vin= 12 V, Ta= 25 °C	1350	---	1800	Vrms
12	Efficiency	η	Vin= 12 V, Load= PANEL	75	---	---	%
13	Striking time	Tscp	Vin= 12 V, Vadj= 0 V	1	---	2	Sec
14	Open Lamp Protection		Latched				
15	Short Lamp Protection		Latched				

Note : The lamp start voltage is tested under one lamp opened Circuit, with a 10cm Hv-wire connected to Hv Probe to simulate lamp wire.

MODEL NAME	TI1502SA-01	DATE	2009/5/7	Code.	3	REV.	A
------------	-------------	------	----------	-------	---	------	---



### 3. INTERFACE SPECIFICATION

Input Connector : CN1  
: CS JS-1125R-05 or equ

Pin No.	Signal	Description
1	Vin	Input Voltage
2	GND	Power System Return
3	ON/OFF	ON/OFF Control
4	Vadj	Lamp Control
5	N.C	N.C

Output Connector : CON3,CON4  
: CS JS-2013-02(M)(LOCK) or equ

Pin No.	Signal	Description
1	Lamp High	High Voltage Output For High Side CCFL
2	Lamp Low	Low Voltage Output For Low Side CCFL


### 4. ENVIRONMENT

Operation Temperature	0 ~ 50 °C
Operation Humidity	90 % Max. RH
Storage Temperature	- 10 ~ 85 °C
Storage Humidity	95 % Max. RH

### 5. TEST EQUIPMENT

Dc Power Supply	<input checked="" type="checkbox"/> Toward 6303D	<input type="checkbox"/> Toward 3306D	
Scope	<input type="checkbox"/> Tektronix TDS1012	<input type="checkbox"/> Tektronix TDS-360	<input checked="" type="checkbox"/> Tektronix TDS2024
	<input type="checkbox"/> Tektronix TDS 3032B	<input type="checkbox"/> Tektronix DPO 4032	
High Voltage Probe	<input checked="" type="checkbox"/> Tektronix P6015A (1000x3.0pF 100MΩ)		
Current Probe	<input type="checkbox"/> Tektronix TM502A	<input type="checkbox"/> Tektronix A6302	<input checked="" type="checkbox"/> Tektronix P6022
	<input checked="" type="checkbox"/> FLUKE45		

MODEL NAME	TI1502SA-01	DATE	2009/5/7	Code.	3	REV.	A
------------	-------------	------	----------	-------	---	------	---



<b>TPEI</b>		TAIWAN POWER CONVERSION INC., LTD			
FILE NAME: T11502SA-01 Code:3		PCB Material Tolerance (mm)			
DATE: 98/05/06		Tolerance (mm)			
Dimension: 153.5 x 26mm (+/-0.5mm)		T	1.0	1.2	1.6
		FR4	+0.20/-0.13	+0.20/-0.13	+0.20/-0.13
		FR1	+0.18/-0.13	+0.18/-0.13	+0.18/-0.13
		CEM1	+0.18/-0.13	+0.18/-0.13	+0.18/-0.13
		TOLERANCE DIM(mm)			
		X.	+/-0.5		
		XX	+/-0.25		
		XXX	+/-0.12		
		XXXX	+/-0.08		