



1203-23-9

NOTES:

1. FOR USE WITH LMR 400 CABLE.
2. FOR CABLING INSTRUCTIONS SEE CP-480.
3. FOR CRIMPING USE DIE KTH-2135.
4. INTERFACE PER MIL-STD-348, FIG. 304-2.
5. CRIMPING SLEEVE AND CENTER CONTACT TO BE SUPPLIED UNASSEMBLED.
6. MATERIALS:

INSULATOR: TEFLON.
 GASKET: SILICONE RUBBER.
 K-GRIP SLEEVE: COMMERCIAL BRONZE.
 C-RING: PHOSPHOR BRONZE.
 OUTER CONTACT: BER. COP.
 ALL OTHER METAL PARTS: BRASS.

7. FINISHES:

CENTER CONTACT: GOLD PLATE.
 OUTER CONTACT: SILVER PLATE.
 ALL OTHER METAL PARTS: NICKEL OR WHITE BRONZE PLATE.
 FOR NICKEL PLATING, ORDER PART NUMBER AS SHOWN. FOR WHITE BRONZE PLATING, ADD "MJ3" SUFFIX TO THE PART NUMBER SHOWN, FOR EXAMPLE 1203-23-9 MJ3.

8. ELECTRICAL CHARACTERISTICS:

NOMINAL IMPEDANCE: 50 OHMS.
 WORKING VOLTAGE: 1000 VRMS.
 FREQUENCY RANGE: DC TO 11 GHZ.

STAMP: KINGS 1203-23-9
 YRWK (DATE CODE)
 (SEE NOTE 7) 5/8-24UNEF-2A THREAD

REVISIONS

ISSUE	CHANGES
0	ER 38383 HVN 08/17/01
1	CN 39971 C DRK 06/18/07

SCALE 4:1

APPROX SURFACE AREA

WAS E-19740

USED ON

REF: 1205-4-9

N, JACK

DRAWN HVN DATE 2/19/00

DESIGN HVN DATE 2/14/00

APPR. DATE

A Winchester Electronics Company

SD

1203-23-9