



AMERICAN MICROSEMICONDUCTOR INC.

P. O. Box 104
 Madison, New Jersey 07940 U.S.A.
<http://www.americanmicrosemi.com>
 email: sales@americanmicrosemi.com
 Phone: (973) 377-9566 Fax: (973) 377-3078

FEATURES

- 16 Diode Array
- Standard 14 pin Ceramic Dual-In-Line Package

MECHANICAL

- Marking: Device number

MAXIMUM RATINGS

- Operating Temperatures: -55°C to +150°C
- Storage Temperature: -65°C to +200°C
- Forward Surge Current: 2.0 Amps (8.3 mS)
- Continuous forward current I_F : 500mA
- Power dissipation (P_D): 500mW
- Derating factor: 4.0mW/°C

PACKAGING

- Carrier tube 25 pcs per (STANDARD)

ELECTRICAL CHARACTERISTICS @ 25°C Unless otherwise specified

Part Number	$V_{(BR)}$ @10 μ A	I_R +25°C	CAP @0V	trr	V_F @ I_F = 10mA	V_F @ I_F = 100mA
	V	μ A	pF	(nS)	V	V
SG6508J	MIN	MAX	MAX	MAX	MAX	MAX
	60	1	4	10	1.0	1.2

