



## Dual P-Channel 30-V (D-S) MOSFET


PRODUCT SUMMARY		
$V_{DS}$ (V)	$r_{DS(on)}$ ( $\Omega$ )	$I_D$ (A)
-30	0.014 @ $V_{GS} = -10$ V	-13.7
	0.025 @ $V_{GS} = -4.5$ V	-10.1

### FEATURES



- TrenchFET® Power MOSFET

### APPLICATIONS

- Battery Switch
- Load Switch



Ordering Information: Si7947DP-T1



ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)					
Parameter	Symbol	10 secs	Steady State	Unit	
Drain-Source Voltage	$V_{DS}$	-30		V	
Gate-Source Voltage	$V_{GS}$	$\pm 20$			
Continuous Drain Current ( $T_J = 150^\circ\text{C}$ ) <sup>a</sup>	$I_D$	$T_A = 25^\circ\text{C}$	-13.7	-8.7	A
		$T_A = 70^\circ\text{C}$	-10.8	-6.9	
Pulsed Drain Current	$I_{DM}$	-30			
continuous Source Current (Diode Conduction) <sup>a</sup>	$I_S$	-2.9	-1.2		
Maximum Power Dissipation <sup>a</sup>	$P_D$	$T_A = 25^\circ\text{C}$	3.5	1.4	W
		$T_A = 70^\circ\text{C}$	2.2	0.9	
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to 150		$^\circ\text{C}$	

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient <sup>a</sup>	$R_{thJA}$	$t \leq 10$ sec	26	35	$^\circ\text{C/W}$
		Steady State	60	85	
Maximum Junction-to-Case (Drain)	$R_{thJC}$	2.5	3.1		

Notes

a. Surface Mounted on 1" x 1" FR4 Board.



**SPECIFICATIONS (T<sub>J</sub> = 25 °C UNLESS OTHERWISE NOTED)**

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250 μA	-1		-3	V
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = -24 V, V <sub>GS</sub> = 0 V			-1	μA
		V <sub>DS</sub> = -24 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 55 °C			-25	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> = -5 V, V <sub>GS</sub> = -10 V	-30			A
Drain-Source On-State Resistance <sup>a</sup>	r <sub>DS(on)</sub>	V <sub>GS</sub> = -10 V, I <sub>D</sub> = -13.7 A		0.011	0.014	Ω
		V <sub>GS</sub> = -4.5 V, I <sub>D</sub> = -10.1 A		0.020	0.025	
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = -10 V, I <sub>D</sub> = -13.7 A		36		S
Diode Forward Voltage <sup>a</sup>	V <sub>SD</sub>	I <sub>S</sub> = -2.9 A, V <sub>GS</sub> = 0 V		-0.8	-1.2	V
<b>Dynamic<sup>b</sup></b>						
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = -15 V, V <sub>GS</sub> = -10 V, I <sub>D</sub> = -13.7 A		45.5	70	nC
Gate-Source Charge	Q <sub>gs</sub>			7		
Gate-Drain Charge	Q <sub>gd</sub>			12.5		
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = -15 V, R <sub>L</sub> = 15 Ω I <sub>D</sub> ≅ -1 A, V <sub>GEN</sub> = -10 V, R <sub>G</sub> = 6 Ω		15	25	ns
Rise Time	t <sub>r</sub>			10	15	
Turn-Off Delay Time	t <sub>d(off)</sub>			135	210	
Fall Time	t <sub>f</sub>			80	120	
Source-Drain Reverse Recovery Time	t <sub>rr</sub>		I <sub>F</sub> = -2.9 A, di/dt = 100 A/μs		70	

Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.


**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**






**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**


**On-Resistance vs. Drain Current**




**Capacitance**




**Gate Charge**




**On-Resistance vs. Junction Temperature**







**Source-Drain Diode Forward Voltage**



**On-Resistance vs. Gate-to-Source Voltage**



**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**





**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**

