



by Honeywell

# Velociti® Series AMM-2F

## Description

The Gamewell-FCI Velociti® Series, addressable monitor module AMM-2F is a single Style B, Class B initiating device circuit (IDC) with a 47KW end-of-line resistor. This module provides an address for any device or group of devices connected to this circuit on the signaling line circuit (SLC) of the Gamewell-FCI addressable series fire alarm control panel. Any initiating device with normally open (N.O.) dry contacts may be made addressable when connected to the AMM-2F module.

The Velociti® Series use a communication protocol that substantially increases the speed of communication between the sensors and certain Gamewell-FCI analog addressable fire alarm controls. These devices operate in a grouped fashion. If one of the devices in the group has a status change, the panel's microprocessor stops the group poll and concentrates on the single device. The net effect is response speed up to five times greater than earlier designs.

The AMM-2F module can be programmed to provide a wide variety of input functions to the Gamewell-FCI addressable series fire alarm control panels. It can be identified as a manual station, heat detector, plenum detector, waterflow switch, tamper switch, N.O. contact, smoke detector, projected beam smoke detector, sub loop, remote zone, etc. It can also serve as a remote system silence, system reset, system acknowledge or drill switch. It is even possible to customize its device type to meet specific job requirements.

The initiating device circuit of the AMM-2F can support a maximum line resistance of up to 40 ohms allowing the use of linear heat detection devices. The compact size facilitates the installation of the module inside manual stations, or mounting boxes of various types of alarm initiating devices.

Velociti® is a registered trademark of Honeywell International Inc.  
UL® is a registered trademark of Underwriters Laboratories Inc.

## Addressable Monitor Module



AMM-2F

## Features

- Compact size allows easy installation
- Class B, Style B, initiating circuit
- 40 Ohm line resistance for each initiating device circuit
- Connects to any normally open dry contact device

## Specifications

**Supervisory Current:** .000375 amps  
**Alarm Current:** .00060 amps  
**Operating Temperature:** 32° to 120° F (0° to 49° C)  
**Relative Humidity:** 10 to 93%  
 (non-condensing)  
**End-of-Line Resistance:** 47K ohms  
**Dimensions:** 1.3" L x 2.5" W x 0.5" D  
 (3.3 x 6.4 x 1.3 cm)

## Ordering Information

Part Number	Description
AMM-2F	Addressable monitor module, single circuit, Style B, Class B

SIGNALING



LISTED  
S1949



APPROVED  
3023594

MEA  
Approved

227-03-E VOL IV 7300-1703:0102



GAMEWELL-FCI  
12 Clintonville Road, Northford, CT 06472-1610 USA • Tel: (203) 484-7161 • Fax: (203) 484-7118

Specifications are for information only, are not intended for installation purposes, and are subject to change without notice. No responsibility is assumed by Gamewell-FCI for their use.

©2013 Honeywell International Inc. All rights reserved.

www.gamewell-fci.com

9020-0626 Rev. E page 1 of 1