






# VL Plus 2 Whites

## Everyday standard face lit solutions

VL Plus 2 LED lighting system is based on proven SloanLED channel letter module design and performance. VL Plus 2 offers a variety of solutions and a wide selection of color temperatures.

- VL Plus 2 is 25% brighter than VL Plus
- **NEW** VL Plus 2 HB Short is 28% brighter than VL Plus 2 Short
- Short available in 5 shades of white
- Constant Current Technology (CCT)



## Specifications

<b>Part number</b>	Long	6500 K	701269-6WLA2-MB
	Short	7200 K	701269-7WSA2-MB
		6500 K	701269-6WSA2-MB
		5000 K	701269-5WSA2-MB
		4000 K	701269-4WSA2-MB
<b>Dimensions L × W × H</b>		3000 K	701269-3WSA2-MB
	HB Short	6500 K	701269-6WHA1-MB
	Mini	6500 K	701269-6WMA2-MB
<b>Viewing angle</b>	Long	3.45 in × 0.49 in × 0.35 in	
	Short	2.35 in × 0.49 in × 0.35 in	
	Mini	1.33 in × 0.44 in × 0.35 in	
<b>LEDs per module</b>	Long/Short	3	
	Mini	2	
<b>Modules per foot</b>	Long	2	
	Short	2.5	
	Mini	4	
<b>Maximum coverage per row</b>	<b>Can depth</b>	<b>Coverage</b>	
	5 in	5 in	
<b>Operating temperature</b>	-40° C to +70° C		
<b>Protection class</b>	IP66		
<b>Power per module</b>	Long/Short	0.54 W	
	Mini	0.42 W	
<b>Efficacy</b>	Long/Short	93 lm/W	
	HB Short	119 lm/W	
	Mini	60 lm/W	
<b>Power capacity</b>	Per SloanLED 60 W 12 VDC power supply:		
	Long/Short	100 modules	
	Mini	128 modules	



# VL Plus 2 Whites

## Everyday standard face lit solutions

### Specifications *cont'd*

<b>Fastening</b>	Peel-n-stick and mechanical	
<b>Packaging</b>	5 trays per carton	
	Long	25 ft (50 modules) per tray
	Short	30 ft (75 modules) per tray
	Mini	25 ft (100 modules) per tray



Size	Color temperature	Part number	Lumens per module (nominal)
Long	6500 K	701269-6WLA2-MB	50
Short	7200 K	701269-7WSA2-MB	50
	6500 K	701269-6WSA2-MB	50
	5000 K	701269-5WSA2-MB	50
	4000 K	701269-4WSA2-MB	50
	3000 K	701269-3WSA2-MB	50
HB Short	6500 K	701269-6WHA1-MB	64
Mini	6500 K	701269-6WMA2-MB	25

