

## 1 Form A Solid State Relay

### Features

- Current Limit Protection
  - Isolation Test Voltage 5300 V<sub>RMS</sub>
  - Typical R<sub>ON</sub> 20 Ω
  - Load Voltage 350 V
  - Load Current 150 mA
  - High Surge Capability
  - Clean Bounce Free Switching
  - Low Power Consumption
  - High Reliability Monolithic output die
  - SMD Lead Available on Tape and Reel
- 
- Lead-free component
  - Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

### Agency Approvals

- UL1577, File No. E52744 System Code H or J, Double Protection
- CSA - Certification 093751
- BSI/BABT Cert. No. 7980
- FIMKO Approval


### Applications

General Telecom Switching

- On/off Hook Control
- Ring Delay
- Dial Pulse
- Ground Start
- Ground Fault Protection

Instrumentation

Industrial Controls



See "Solid State Relays" (Application Note 56)

### Description

The LH1500 is robust, ideal for telecom and ground fault applications. It is a SPST normally open switch (1 Form A) that replaces electromechanical relays in many applications. It is constructed using a GaAlAs LED for actuation control and an integrated monolithic die for the switch output. The die, fabricated in a high-voltage dielectrically isolated technology, is comprised of a photodiode array, switch control circuitry and MOSFET switches. In addition, it employs current-limiting circuitry which meets FCC 68.302 and other regulatory voltage surge requirements when overvoltage protection is provided.

### Order Information

Part	Remarks
LH1500AT	Thru Hole, DIP-6
LH1500AAB	SMD-6
LH1500AABTR	Tape and Reel, SMD-6

### Absolute Maximum Ratings, $T_{amb} = 25\text{ }^{\circ}\text{C}$

Stresses in excess of the absolute Maximum Ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute Maximum Ratings for extended periods of time can adversely affect reliability.

### SSR

Parameter	Test condition	Symbol	Value	Unit
SSR output power dissipation (continuous)		$P_{diss}$	550	mW
LED reverse voltage	$I_R \leq 10\text{ mA}$	$V_R$	8.0	V
LED continuous forward current		$I_F$	50	mA
DC or Peak AC load voltage	$I_L \leq 50\text{ mA}$	$V_L$	350	V
Continuous DC load current - bidirectional	$T_{amb} = 25\text{ }^{\circ}\text{C}$	$I_L$	150	mA
Continuous DC load current - unidirectional	$T_{amb} = 25\text{ }^{\circ}\text{C}$	$I_L$	250	mA
Ambient temperature range		$T_{amb}$	- 40 to + 85	$^{\circ}\text{C}$
Storage temperature range		$T_{stg}$	- 40 to + 150	$^{\circ}\text{C}$
Soldering temperature	$t = 10\text{ s max.}$	$T_{sld}$	260	$^{\circ}\text{C}$
Isolation test voltage (for 1.0 s)		$V_{ISO}$	5300	$V_{RMS}$
Isolation resistance	$V_{IO} = 500\text{ V}, T_{amb} = 25\text{ }^{\circ}\text{C}$	$R_{IO}$	$\geq 10^{12}$	$\Omega$
	$V_{IO} = 500\text{ V}, T_{amb} = 100\text{ }^{\circ}\text{C}$	$R_{IO}$	$\geq 10^{11}$	$\Omega$

### Electrical Characteristics, $T_{amb} = 25\text{ }^{\circ}\text{C}$

Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluations. Typical values are for information only and are not part of the testing requirements.

### Input

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
LED forward current, switch turn-on	$I_L = 100\text{ mA}, t = 10\text{ ms}$	$I_{Fon}$		0.9	2.0	mA
LED forward current, switch turn-off	$V_L = \pm 300\text{ V}$	$I_{Foff}$	0.2	0.8		mA
LED forward voltage	$I_F = 10\text{ mA}$	$V_F$	1.15	1.25	1.45	V


### Output

Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
ON-resistance, ac/dc: Pin 4 ( $\pm$ ) to 6 ( $\pm$ )	$I_F = 5.0\text{ mA}, I_L = 50\text{ mA}$	$R_{ON}$		20	25	$\Omega$
ON-resistance, dc: Pin 4, 6 (+) to 5 (-)	$I_F = 5.0\text{ mA}, I_L = 100\text{ mA}$	$R_{ON}$	3.0	4.6	6.25	$\Omega$
Off-resistance	$I_F = 0\text{ mA}, V_L = \pm 100$	$R_{OFF}$	0.5	300		$G\Omega$
Current limit ac/dc: pin 4 ( $\pm$ ) to 6 ( $\pm$ )	$I_F = 5.0, t = 5.0\text{ ms}, V_L = \pm 6.0\text{ V}$	$I_{LMT}$	230	255	370	mA
Off-state leakage current	$I_F = 0\text{ mA}, V_L = \pm 100\text{ V}$	$I_O$		0.32	200	nA
	$I_F = 0\text{ mA}, V_L = \pm 350\text{ V}$	$I_O$			1.0	$\mu\text{A}$
Output capacitance, Pin 4 to 6	$I_F = 0\text{ mA}, V_L = 1.0\text{ V}$	$C_O$		33		pF
	$I_F = 0\text{ mA}, V_L = 50\text{ V}$	$C_O$		10		pF
Switch offset	$I_F = 5.0\text{ mA}$	$V_{OS}$		0.2		$\mu\text{V}$

## Transfer


Parameter	Test condition	Symbol	Min	Typ.	Max	Unit
Capacitance (input-output)	$V_{ISO} = 1.0\text{ V}$	$C_{IO}$		0.71		pF
Turn-on time	$I_F = 5.0\text{ mA}$ , $I_L = 50\text{ mA}$	$t_{on}$		0.3	2.0	ms
Turn-off time	$I_F = 5.0\text{ mA}$ , $I_L = 50\text{ mA}$	$t_{off}$		0.6	2.0	ms

## Typical Characteristics ( $T_{amb} = 25\text{ }^\circ\text{C}$ unless otherwise specified)




ih1500at\_00

Figure 1. Recommended Operating Conditions




ih1500at\_02

Figure 3. LED Forward Current vs. Forward Voltage




ih1500at\_01

Figure 2. LED Voltage vs. Temperature




ih1500at\_03

Figure 4. LED Reverse Current vs. LED Reverse Voltage




ih1500at\_04

Figure 5. LED Current for Switch Turn-on vs. Temperature




ih1500at\_07

Figure 8. Load Current vs. Load Voltage




ih1500at\_05

Figure 6. LED Dropout Voltage vs. Temperature




ih1500at\_08

Figure 9. ON-Resistance vs. Temperature




ih1500at\_06

Figure 7. Current Limit vs. Temperature




ih1500at\_09

Figure 10. Variation in ON-Resistance vs. LED Current




ih1500at\_10

Figure 11. Switch Capacitance vs. Applied Voltage




ih1500at\_13

Figure 14. Output Isolation




ih1500at\_11

Figure 12. Insertion Loss vs. Frequency




ih1500at\_14

Figure 15. Switch Breakdown Voltage vs. Load Current




ih1500at\_12

Figure 13. Leakage Current vs. Applied Voltage




ih1500at\_15

Figure 16. Switch Breakdown Voltage vs. Temperature




ih1500at\_16

Figure 17. Switch Offset Voltage vs. Temperature




ih1500at\_19

Figure 20. Turn-off Time vs. Temperature




ih1500at\_17

Figure 18. Switch Offset Voltage vs. LED Current




ih1500at\_20

Figure 21. Turn-on Time vs. LED Current



ih1500at\_18

Figure 19. Turn-on Time vs. Temperature




ih1500at\_21

Figure 22. Turn-off Time vs. LED Current


## Package Dimensions in Inches (mm)

### DIP



## Package Dimensions in Inches (mm)

### SMD



### Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design  
and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany  
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423





---

**Notice**

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.