



N-Channel MOSFET

AO3422-HF (KO3422-HF)

■ Features

- $V_{DS} (V) = 55V$
- $I_D = 2.1 A (V_{GS} = 4.5V)$
- $R_{DS(ON)} < 160m\Omega (V_{GS} = 4.5V)$
- $R_{DS(ON)} < 200m\Omega (V_{GS} = 2.5V)$
- Pb-Free Package May be Available. The G-Suffix Denotes a Pb-Free Lead Finish



■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit	
Drain-Source Voltage	V_{DS}	55	V	
Gate-Source Voltage	V_{GS}	± 12		
Continuous Drain Current	I_D	$T_A=25^\circ C$	2.1	A
		$T_A=70^\circ C$	1.7	
Pulsed Drain Current	I_{DM}	10		
Power Dissipation	P_D	$T_A=25^\circ C$	1.25	W
		$T_A=70^\circ C$	0.8	
Thermal Resistance.Junction- to-Ambient	R_{thJA}	$t \leq 10s$	100	$^\circ C/W$
		Steady-State	150	
Thermal Resistance.Junction- to-Case	R_{thJC}	60		
Junction Temperature	T_J	150	$^\circ C$	
Storage Temperature Range	T_{stg}	-55 to 150		

N-Channel MOSFET

AO3422-HF (K03422-HF)

■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	V _{DSS}	I _D =10 mA, V _{GS} =0V	55			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =44V, V _{GS} =0V			1	μA
		V _{DS} =44V, V _{GS} =0V, T _J =55°C			5	
Gate-Body Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±12V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250 μA	0.6		2	V
Static Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =4.5V, I _D =2.1A			160	mΩ
		V _{GS} =4.5V, I _D =2.1A, T _J =125°C			210	
		V _{GS} =2.5V, I _D =1.5A			200	
On state drain current	I _{D(ON)}	V _{GS} =4.5V, V _{DS} =5V	10			A
Forward Transconductance	g _{FS}	V _{DS} =5V, I _D =2.1A		11		S
Input Capacitance	C _{iss}	V _{GS} =0V, V _{DS} =25V, f=1MHz		214	300	pF
Output Capacitance	C _{oss}			31		
Reverse Transfer Capacitance	C _{rss}			12.6		
Gate Resistance	R _g		V _{GS} =0V, V _{DS} =0V, f=1MHz		1.3	
Total Gate Charge	Q _g	V _{GS} =4.5V, V _{DS} =27.5V, I _D =2.1A		2.6	3.3	nC
Gate Source Charge	Q _{gs}			0.6		
Gate Drain Charge	Q _{gd}			0.8		
Turn-On DelayTime	t _{d(on)}		V _{GS} =10V, V _{DS} =27.5V, R _L =12Ω, R _G =3Ω		2.3	
Turn-On Rise Time	t _r			2.4		
Turn-Off DelayTime	t _{d(off)}			16.5		
Turn-Off Fall Time	t _f			2		
Body Diode Reverse Recovery Time	t _{rr}	I _F = 2.1A, di/dt= 100A/us			20	30
Body Diode Reverse Recovery Charge	Q _{rr}			17		nC
Maximum Body-Diode Continuous Current	I _S				1	A
Diode Forward Voltage	V _{SD}	I _S =1A, V _{GS} =0V			1	V

* The static characteristics in Figures 1 to 6 are obtained using <300us pulses, duty cycle 0.5% max.

■ Marking

Marking	AR** _F
---------	-------------------

N-Channel MOSFET AO3422-HF (KO3422-HF)

■ Typical Characteristics




Fig 1: On-Region characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

N-Channel MOSFET AO3422-HF (KO3422-HF)

■ Typical Characteristics




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance