

**isc N-Channel MOSFET Transistor**

**2SK1401A**

**DESCRIPTION**

- Drain Current  $-I_D = 15A @ T_C = 25^\circ C$
- Drain Source Voltage-  
:  $V_{DSS} = 350V(\text{Min})$
- Fast Switching Speed

**APPLICATIONS**



- high speed power switching

**ABSOLUTE MAXIMUM RATINGS( $T_a = 25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{DSS}$	Drain-Source Voltage ( $V_{GS} = 0$ )	350	V
$V_{GS}$	Gate-Source Voltage	$\pm 30$	V
$I_D$	Drain Current-continuous @ $T_C = 25^\circ C$	15	A
$P_{tot}$	Total Dissipation @ $T_C = 25^\circ C$	100	W
$T_j$	Max. Operating Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature Range	-55~150	$^\circ C$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th j-c}$	Thermal Resistance, Junction to Case	0.83	$^\circ C/W$
$R_{th j-a}$	Thermal Resistance, Junction to Ambient	35	$^\circ C/W$



## isc N-Channel Mosfet Transistor

## 2SK1401A

• ELECTRICAL CHARACTERISTICS (T<sub>C</sub>=25°C)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0; I <sub>D</sub> = 10mA	350			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =10 V <sub>GS</sub> ; I <sub>D</sub> =1mA	2.0		3.0	V
R <sub>DS(on)</sub>	Drain-Source On-stage Resistance	V <sub>GS</sub> =10V; I <sub>D</sub> =8A		0.30	0.40	Ω
I <sub>GSS</sub>	Gate Source Leakage Current	V <sub>GS</sub> = ±25V; V <sub>DS</sub> = 0			±10	uA
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =280V; V <sub>GS</sub> = 0			250	uA
V <sub>SD</sub>	Diode Forward Voltage	I <sub>F</sub> =15A; V <sub>GS</sub> =0		1.05		V
t <sub>r</sub>	Rise time	V <sub>GS</sub> =10V; I <sub>D</sub> =8A; R <sub>L</sub> =3.75 Ω		80		ns
t <sub>on</sub>	Turn-on time			95		ns
t <sub>f</sub>	Fall time			55		ns
t <sub>off</sub>	Turn-off time			155		ns