

DRJ30-12-1 New Product



Sales Region	Worldwide
Series	DRJ
Status	Production
Feature	DIN rail installation compatible
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics

Input Voltage Range[AC]	85 to 264V
Input Voltage Range[DC]	120 to 370V
Efficiency	85.5% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	10.8 to 15V
Maximum Output Current	2.3A
Maximum Output Power	27.6W

Cases Shape & Size

Case'□ shape	DIN rail
Width(W)	21.5mm Nom.
Height(H)	75mm Nom.
Depth(D)	90mm Nom.
Weight	120g Typ.

Other

Operating Temp. Range	-20 to 70°C
Cooling	Convection cooling
Safety Standard(Certified)	UL60950-1
	CSA C22.2 No.60950-1
	CSA C22.2 No.107.1
	EN60950-1
Safety Standard(Conformed)	UL508
	Den-an Appendix 8 at 100VAC only
Remarks	This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.