



All dimensions are in mm; tolerances according to ISO 2768 m-H

Description

This weather proofing kit provides additional sealing for mated 4.1-9.5 or 4.3-10 connections. The sealing is field installable on factory made jumpers and is UV protected.

Documents

Assembly instruction

MA_SLWK101-C03

Material for connectors

Parts

Sealing:
Clamping Part:
Locking Sleeve:
Mounting guide

Material

oil bleeding silicone
PA
PBT
PP

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG
RF_35/06.10/1.0

Mechanical data*

Mating cycles > 25
 Suitable cable diameter 13 - 17 mm
 Suitable connector diameter 17 – 20 mm

Environmental data*

Operation temperature range -40°C to +70°C
 Storage temperature range -40°C to +90°C
 Degree of protection* IEC 60529, IP68 1bar 1 h
 Water immersion IEC 60169-1, Sub-clause 14.7
 Termal shock IEC 60169-1, Sub-clause 16.4
 Salt mist IEC 60169-1 Sub-clause 16.7 (672h)
 RoHS compliant

Weight

Weight tbd g / pce

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
M. Wimmer	07.04.2014	M. Wimmer	18.03.2015	400	15-v083	Tobi Stadler	18.03.2015
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page
							2 / 2

RF_35/06.10/1.0